COMPACT LED EVO N 4800LM PLX II KL IP65 620X620 840 (42W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK07
Nominal power [W]:	42
Luminous flux [lm]*:	4800
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	E
Material of the body:	ABS
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Compact LED luminaire designed for surface mounting. Equipped with energy-saving LED panels and an evenly highlighted opal diffuser, providing low glare (UGR<19)*. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Special brackets for mounting COMPACT lamps in surface-mounted version for use on uneven ceilings. These holders ensure a solid fixing while maintaining the distance between the ceiling and the lamp.

* The UGR coefficient is met for the typical use of the luminaire

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting’s design is suitable for mounting in 600x600 modular ceilings.

COMPACT LED EVO N 4800LM PLX II KL IP65 620X620 840 (42W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	628283
EAN:	5905963628283
Light source:	LED module
Rated power of the luminaire [W]:	43
Nominal power [W]:	42
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	4800
Luminous efficacy [lm/W]:	111
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.90
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	OPAL
Diffuser colour:	white
Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	66/620/620/0
Mounting dimensions [mm]:	525/410

Impact resistance:	IK07
Ingress protection:	IP65
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Number on the palette [pcs]:	40
Net weight [kg]:	3.400
Category type:	troffers
AC voltage range [V]:	198 - 264
UGR (4H8H):	17,8-24,3
LED lifespan L70B50 [h]:	125000
LED lifespan L80B10 [h]:	82000
LED lifespan L90B10 [h]:	40000
ETIM class:	EC002892
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Warranty [years]:	5
CE certificate:	357/2023
ENEC Certificate:	
PZH certificate:	B-BK-60112-0326/2026
Environmental Product Declaration (EPD):	944/2026
Manual:	Download PDF
ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Plik LDT:	Download


LIGHT CURVES



COMPACT LED EVO N 4800LM PLX II KL IP65 620X620 840 (42W)

DETAILED CARD

TECHNICAL DETAILS




COMPACT LED EVO N IP65

COMPACT LED EVO N 4800LM PLX II KL IP65 620X620 840 (42W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
630279	Compact - Uchwyt do mocowania natynkowego - specjalny / Holder for surface mounting - special



Compact - Uchwyt do mocowania natynkowego - specjalny / Holder for surface mounting - special (630279)

Card creation date: 15 October 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 357/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl