

# NECTRA LED PLUS 121MM 500LM 830 IP44 OPAL WHITE (5W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	517792
<b>Ingress protection:</b>	IP44
<b>Nominal power [W]:</b>	5
<b>Luminous flux [lm]*:</b>	500
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	>80
<b>Energy efficiency class:</b>	F
<b>Material of the body:</b>	PC, aluminium
<b>Colour of the body:</b>	white
<b>Diffuser material:</b>	PMMA

## CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.

## APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

# NECTRA LED PLUS 121MM 500LM 830 IP44 OPAL WHITE (5W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Nominal power [W]:</b>	5	<b>Colour of the body:</b>	white
<b>Light source:</b>	LED module	<b>Ring material:</b>	PC
<b>Colour temperature [K]:</b>	3000	<b>Ring colour:</b>	white
<b>Luminous flux [lm]:</b>	500	<b>Mounting dimensions [mm]:</b>	ø100
<b>Rated power of the luminaire [W]:</b>	6	<b>Impact resistance:</b>	IK08
<b>Diffuser type:</b>	OPAL	<b>Ingress protection:</b>	IP44
<b>Supply voltage [V]:</b>	220-240	<b>Mounting version:</b>	recessed
<b>Frequency [Hz]:</b>	50 - 60	<b>Working temperature [°C]:</b>	from -10 to +35
<b>Luminous efficacy [lm/W]:</b>	83	<b>Net weight [kg]:</b>	0.250
<b>Dimensions (H/W/T/S) [mm]:</b>	ø121/67	<b>CE certificate:</b>	<a href="#">340/2023</a>
<b>Energy efficiency class:</b>	F	<b>Warranty [years]:</b>	5
<b>Electrical protection class:</b>	II	<b>Index:</b>	517792
<b>Colour rendering index:</b>	>80	<b>EAN:</b>	5905963517792
<b>SDCM:</b>	≤ 3	<b>Category type:</b>	downlights
<b>Power factor:</b>	0.58	<b>Luminaire rated power <math>P_{min}</math> [W]:</b>	5.93
<b>Beam angle [°]:</b>	88	<b>AC voltage range [V]:</b>	198 - 264
<b>Diffuser material:</b>	PMMA	<b>LED lifespan L70B50 [h]:</b>	80000
<b>Optics material:</b>	aluminium	<b>LED lifespan L80B20 [h]:</b>	55000
<b>Optics:</b>	reflector	<b>LED lifespan L90B10 [h]:</b>	30000
<b>Material of the body:</b>	PC, aluminium	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
		<b>Warranty [years]:</b>	5
		<b>Manual:</b>	<a href="#">Download PDF</a>
		<b>Plik LDT:</b>	<a href="#">Download</a>

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 340/2023