

NECTRA LED PLUS 121MM 500LM 830 IP44 OPAL WHITE (5W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	517792
Ingress protection:	IP44
Nominal power [W]:	5
Luminous flux [lm]*:	500
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Energy efficiency class:	F
Material of the body:	PC + aluminium
Colour of the body:	white
Diffuser material:	PMMA

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

NECTRA LED PLUS 121MM 500LM 830 IP44 OPAL WHITE (5W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	517792	Optics:	reflector
EAN:	5905963517792	Material of the body:	PC + aluminium
Light source:	LED module	Colour of the body:	white
Nominal power [W]:	5	Ring material:	PC
Rated power of the luminaire [W]:	6	Ring colour:	white
Supply voltage [V]:	220-240	Dimensions (H/W/T/S) [mm]:	ø121/67
Frequency [Hz]:	50 - 60	Mounting dimensions [mm]:	ø100
Luminous flux [lm]:	500	Impact resistance:	IK08
Luminous efficacy [lm/W]:	83	Ingress protection:	IP44
Energy efficiency class:	F	Mounting version:	recessed
Electrical protection class:	II	Working temperature [°C]:	from -10 to +35
Colour temperature [K]:	3000	Number on the palette [pcs]:	1122
Color rendering index (Ra) >:	80	Net weight [kg]:	0.250
SDCM:	3	Category type:	downlights
Power factor:	0.58	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L70B50 [h]:	80000	Warranty [years]:	5
LED lifespan L80B10 [h]:	55000	CE certificate:	340/2023
LED lifespan L90B10 [h]:	30000	Environmental Product Declaration (EPD):	944/2026
Beam angle [°]:	88	Manual:	Download PDF
Diffuser material:	PMMA	ISO Certificates:	9001:2015. 14001:2015. 45001:2018. 50001:2018
Diffuser type:	OPAL	Plik LDT:	Download
Optics material:	aluminium		

Card creation date: 29 April 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 340/2023