

NECTRA LED PLUS 121MM 500LM 830 IP44 OPAL WHITE (5W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	517792
Ingress protection:	IP44
Nominal power [W]:	5
Luminous flux [lm]*:	500
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	F
Material of the body:	PC, aluminium
Colour of the body:	white
Diffuser material:	PMMA

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

NECTRA LED PLUS 121MM 500LM 830 IP44 OPAL WHITE (5W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	5	Colour of the body:	white
Light source:	LED module	Ring material:	PC
Colour temperature [K]:	3000	Ring colour:	white
Luminous flux [lm]:	500	Mounting dimensions [mm]:	ø100
Rated power of the luminaire [W]:	6	Impact resistance:	IK08
Diffuser type:	OPAL	Ingress protection:	IP44
Supply voltage [V]:	220-240	Mounting version:	recessed
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -10 to +35
Luminous efficacy [lm/W]:	83	Net weight [kg]:	0.250
Dimensions (H/W/T/S) [mm]:	ø121/67	CE certificate:	340/2023
Energy efficiency class:	F	Warranty [years]:	5
Electrical protection class:	II	Index:	517792
Colour rendering index:	>80	EAN:	5905963517792
SDCM:	≤ 3	Category type:	downlights
Power factor:	0.58	Luminaire rated power P_{min} [W]:	5.93
Beam angle [°]:	88	AC voltage range [V]:	198 - 264
Diffuser material:	PMMA	LED lifespan L70B50 [h]:	80000
Optics material:	aluminium	LED lifespan L80B20 [h]:	55000
Optics:	reflector	LED lifespan L90B10 [h]:	30000
Material of the body:	PC, aluminium	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
		Warranty [years]:	5
		Manual:	Download PDF
		Plik LDT:	

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 340/2023