

# NECTRA LED PLUS 121MM 930LM 840 IP44 OPAL WHITE (9W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	517709
<b>Ingress protection:</b>	IP44
<b>Nominal power [W]:</b>	9
<b>Luminous flux [lm]*:</b>	930
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	>80
<b>Energy efficiency class:</b>	F
<b>Material of the body:</b>	PC, aluminium
<b>Colour of the body:</b>	white
<b>Diffuser material:</b>	PMMA

## CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.

## APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

# NECTRA LED PLUS 121MM 930LM 840 IP44 OPAL WHITE (9W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	9	Colour of the body:	white
Light source:	LED module	Ring material:	PC
Colour temperature [K]:	4000	Ring colour:	white
Luminous flux [lm]:	930	Mounting dimensions [mm]:	ø100
Rated power of the luminaire [W]:	10	Impact resistance:	IK08
Diffuser type:	OPAL	Ingress protection:	IP44
Supply voltage [V]:	220-240	Mounting version:	recessed
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -10 to +35
Luminous efficacy [lm/W]:	93	Net weight [kg]:	0.250
Dimensions (H/W/T/S) [mm]:	ø121/67	CE certificate:	<a href="#">340/2023</a>
Energy efficiency class:	F	Warranty [years]:	5
Electrical protection class:	II	Index:	517709
Colour rendering index:	>80	EAN:	5905963517709
SDCM:	≤ 3	Category type:	downlights
Power factor:	0.79	Luminaire rated power $P_{min}$ [W]:	10.30
Beam angle [°]:	88	AC voltage range [V]:	198 - 264
Diffuser material:	PMMA	LED lifespan L70B50 [h]:	80000
Optics material:	aluminium	LED lifespan L80B20 [h]:	55000
Optics:	reflector	LED lifespan L90B10 [h]:	30000
Material of the body:	PC, aluminium	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
		Warranty [years]:	5
		Manual:	<a href="#">Download PDF</a>
		Plik LDT:	<a href="#">Pobierz</a>

Card creation date: 23 February 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 340/2023