

NECTRA LED PLUS 170MM 1550LM 830 IP44 DALI AW 3H AT OPAL WHITE (12W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	517693
Ingress protection:	IP44
Nominal power [W]:	12
Luminous flux [lm]*:	1550
Colour temperature [K]:	3000
Colour rendering index:	80
Energy efficiency class:	E
Material of the body:	PC + aluminium
Colour of the body:	white
Diffuser material:	PMMA

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

NECTRA LED PLUS 170MM 1550LM 830 IP44 DALI AW 3H AT OPAL WHITE (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Mounting dimensions [mm]:	ø150
Nominal power [W]:	12	Impact resistance:	IK08
Rated power of the luminaire [W]:	14	Ingress protection:	IP44
Supply voltage [V]:	220-240	Mounting version:	recessed
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from 0 to +35
Luminous flux [lm]:	1550	Emergency lighting [h]:	3
Luminous efficacy [lm/W]:	110	DIMM 1-10V:	yes
Energy efficiency class:	E	DIMM DALI:	yes
Electrical protection class:	I	Net weight [kg]:	0.820
Colour temperature [K]:	3000	CE certificate:	340/2023
Colour rendering index:	80	Warranty [years]:	2 / 0.5 (bateria)
SDCM:	≤ 3	Index:	517693
Power factor:	0.87	EAN:	5905963517693
Charging time [h:min]:	24:00	Category type:	downlights
Beam angle [°]:	92,2	Autotest:	yes
Battery:	Ni-Mh	Operating mode:	M
Diffuser material:	PMMA	Luminaire rated power P_{min} [W]:	14.21
Diffuser type:	OPAL	AC voltage range [V]:	198 - 264
Optics material:	aluminium	DC voltage range [V]:	196 - 280
Optics:	reflector	LED lifespan L70B50 [h]:	80000
Material of the body:	PC + aluminium	LED lifespan L80B20 [h]:	55000
Colour of the body:	white	LED lifespan L90B10 [h]:	30000
Ring material:	PC	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Ring colour:	white	Warranty [years]:	2 / 0.5 (battery)
Dimensions (H/W/T/S) [mm]:	ø170/69	Manual:	Download PDF

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 340/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl