NECTRA LED PLUS 170MM 1650LM 840 IP44 OPAL WHITE (12W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:517624Ingress protection:IP44Nominal power [W]:12Luminous flux [Im]*:1650Colour temperature [K]:4000Colour rendering index:>80Energy efficiency class:D

Material of the body: PC, aluminium

Colour of the body: white

Diffuser material: PMMA

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Its distinctive features are low profile, light weight and very easy and fast installation.

Design for both solid and modular ceilings.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.



NECTRA LED PLUS 170MM 1650LM 840 IP44 OPAL WHITE (12W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source: LED module Nominal power [W]: 12 Rated power of the luminaire [W]: 14 Supply voltage [V]: 110 - 277 Frequency [Hz]: 50 - 60 Luminous flux [lm]: 1650 Luminous efficacy [lm/W]: 117	
Rated power of the luminaire [W]: 14 Supply voltage [V]: 110 - 277 Frequency [Hz]: 50 - 60 Luminous flux [Im]: 1650	
Supply voltage [V]: 110 - 277 Frequency [Hz]: 50 - 60 Luminous flux [Im]: 1650	
Frequency [Hz]: 50 - 60 Luminous flux [Im]: 1650	
Luminous flux [lm]: 1650	
. ,	
Luminous efficacy [lm/W]: 117	
Energy efficiency class:	
Electrical protection class:	
Colour temperature [K]: 4000	
Colour rendering index: >80	
SDCM: ≤ 3	
Power factor: 0.76	
Beam angle [°]: 92.2	
Diffuser material: PMMA	
Diffuser type: OPAL	
Optics material: aluminium	
Optics: reflector	
Material of the body: PC, aluminium	
Colour of the body: white	
Colour of the body: white Ring material: PC	

Dimensions (H/W/T/S) [mm]:	ø170/69
Mounting dimensions [mm]:	ø150
Impact resistance:	IK08
Ingress protection:	IP44
Mounting version:	recessed
Working temperature [°C]:	from -10 to +35
Net weight [kg]:	0.380
CE certificate:	340/2023
Warranty [years]:	5
Index:	517624
EAN:	5905963517624
Category type:	downlights
Luminaire rated power Omin [W]:	14.40
AC voltage range [V]:	99 - 305
DC voltage range [V]:	99 - 305
LED lifespan L70B50 [h]:	80000
LED lifespan L80B20 [h]:	55000
LED lifespan L90B10 [h]:	30000
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	5
Manual:	Download PDF

Card creation date: 07 October 2022



