

# NECTRA LED PLUS 170MM 1650LM 840 IP44 OPAL WHITE (12W)

DETAILED CARD



## TECHNICAL PARAMETERS

|                          |               |
|--------------------------|---------------|
| Index:                   | 517624        |
| Ingress protection:      | IP44          |
| Nominal power [W]:       | 12            |
| Luminous flux [lm]*:     | 1650          |
| Colour temperature [K]:  | 4000          |
| Colour rendering index:  | >80           |
| Energy efficiency class: | D             |
| Material of the body:    | PC, aluminium |
| Colour of the body:      | white         |
| Diffuser material:       | PMMA          |

## CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Its distinctive features are low profile, light weight and very easy and fast installation.

Design for both solid and modular ceilings.

## APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

# NECTRA LED PLUS 170MM 1650LM 840 IP44 OPAL WHITE (12W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |               |                                      |   |
|-----------------------------------|---------------|--------------------------------------|---|
| Light source:                     | LED module    | Mounting dimensions [mm]:            | ø150  |
| Nominal power [W]:                | 12            | Impact resistance:                   | IK08  |
| Rated power of the luminaire [W]: | 14            | Ingress protection:                  | IP44  |
| Supply voltage [V]:               | 110 - 277     | Mounting version:                    | recessed  |
| Frequency [Hz]:                   | 50 - 60       | Working temperature [°C]:            | from -10 to +35   |
| Luminous flux [lm]:               | 1650          | Net weight [kg]:                     | 0.380   |
| Luminous efficacy [lm/W]:         | 117           | CE certificate:                      | <a href="#">340/2023</a>  |
| Energy efficiency class:          | D             | Warranty [years]:                    | 5   |
| Electrical protection class:      | II            | Index:                               | 517624  |
| Colour temperature [K]:           | 4000          | EAN:                                 | 5905963517624   |
| Colour rendering index:           | >80           | Category type:                       | downlights  |
| SDCM:                             | ≤ 3           | Luminaire rated power $P_{min}$ [W]: | 14.40   |
| Power factor:                     | 0.76          | AC voltage range [V]:                | 99 - 305  |
| Beam angle [°]:                   | 92.2          | DC voltage range [V]:                | 99 - 305  |
| Diffuser material:                | PMMA          | LED lifespan L70B50 [h]:             | 80000   |
| Diffuser type:                    | OPAL          | LED lifespan L80B20 [h]:             | 55000   |
| Optics material:                  | aluminium     | LED lifespan L90B10 [h]:             | 30000   |
| Optics:                           | reflector     | Photobiological safety:              | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Material of the body:             | PC, aluminium | Warranty [years]:                    | 5   |
| Colour of the body:               | white         | Manual:                              | <a href="#">Download PDF</a>  |
| Ring material:                    | PC            | ETIM class:                          | EC002892  |
| Ring colour:                      | white         | Plik LDT:                            | <a href="#">Download</a>  |
| Dimensions (H/W/T/S) [mm]:        | ø170/69       |                                      |   |

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 340/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)