NECTRA LED PLUS 170MM 1950LM 830 IP44 DALI AW 3H AT OPAL WHITE (15W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:517617Ingress protection:IP44Nominal power [W]:15Luminous flux [Im]*:1950Colour temperature [K]:3000Color rendering index (Ra) >:80Energy efficiency class:E

Material of the body: PC + aluminium

Colour of the body:whiteDiffuser material:PMMA

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.



NECTRA LED PLUS 170MM 1950LM 830 IP44 DALI AW 3H AT OPAL WHITE (15W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	15
Rated power of the luminaire [W]:	17
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	1950
Luminous efficacy [lm/W]:	114
Energy efficiency class:	E
Electrical protection class:	1
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.96
Charging time [h:min]:	24:00
Beam angle [°]:	92,2
Battery:	Ni-Mh
Diffuser material:	PMMA
Diffuser type:	OPAL
Optics material:	aluminium
Optics:	reflector
Material of the body:	PC + aluminium
Colour of the body:	white
Ring material:	PC
Ring colour:	white
Dimensions (H/W/T/S) [mm]:	ø170/69

Mounting dimensions [mm]:	ø150
Impact resistance:	IK08
Ingress protection:	IP44
Mounting version:	recessed
Working temperature [°C]:	from 0 to +35
Emergency lighting [h]:	3
DIMM 1-10V:	yes
DIMM DALI:	
	yes 0.820
Net weight [kg]: CE certificate:	
	340/2023
Warranty [years]:	2 / 0.5 (bateria)
Index:	517617
EAN:	5905963517617
Category type:	downlights
Autotest:	yes
Operating mode:	M
Luminaire rated power 0min [W]:	16.37
AC voltage range [V]:	198 - 264
DC voltage range [V]:	196 - 280
LED lifespan L70B50 [h]:	80000
LED lifespan L80B20 [h]:	55000
LED lifespan L90B10 [h]:	30000
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	2 / 0.5 (battery)
Manual:	Download PDF

Card creation date: 09 January 2025



