

# NECTRA LED PLUS 222MM 2000LM 830 IP44 DALI OPAL WHITE (15W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	517495
<b>Ingress protection:</b>	IP44
<b>Nominal power [W]:</b>	15
<b>Luminous flux [lm]*:</b>	2000
<b>Colour temperature [K]:</b>	3000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	PC + aluminium
<b>Colour of the body:</b>	white
<b>Diffuser material:</b>	PMMA

## CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.

## APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

# NECTRA LED PLUS 222MM 2000LM 830 IP44 DALI OPAL WHITE (15W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	517495	<b>Material of the body:</b>	PC + aluminium
<b>EAN:</b>	5905963517495	<b>Colour of the body:</b>	white
<b>Light source:</b>	LED module	<b>Ring material:</b>	PC
<b>Nominal power [W]:</b>	15	<b>Ring colour:</b>	white
<b>Rated power of the luminaire [W]:</b>	17	<b>Dimensions (H/W/T/S) [mm]:</b>	ø222/70
<b>Supply voltage [V]:</b>	220-240	<b>Mounting dimensions [mm]:</b>	ø195
<b>Frequency [Hz]:</b>	50 - 60	<b>Impact resistance:</b>	IK08
<b>Luminous flux [lm]:</b>	2000	<b>Ingress protection:</b>	IP44
<b>Luminous efficacy [lm/W]:</b>	117	<b>Mounting version:</b>	recessed
<b>Energy efficiency class:</b>	D	<b>Working temperature [°C]:</b>	from -10 to +35
<b>Electrical protection class:</b>	II	<b>DIMM 1-10V:</b>	yes
<b>Colour temperature [K]:</b>	3000	<b>DIMM DALI:</b>	yes
<b>Color rendering index (Ra) &gt;:</b>	80	<b>Number on the palette [pcs]:</b>	306
<b>SDCM:</b>	3	<b>Net weight [kg]:</b>	0.590
<b>Power factor:</b>	0.96	<b>Category type:</b>	downlights
<b>LED lifespan L70B50 [h]:</b>	80000	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>LED lifespan L80B10 [h]:</b>	55000	<b>Warranty [years]:</b>	5
<b>LED lifespan L90B10 [h]:</b>	30000	<b>CE certificate:</b>	<a href="#">340/2023</a>
<b>Beam angle [°]:</b>	96	<b>Environmental Product Declaration (EPD):</b>	<a href="#">944/2026</a>
<b>Diffuser material:</b>	PMMA	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Diffuser type:</b>	OPAL	<b>ISO Certificates:</b>	9001:2015. 14001:2015. 45001:2018. 50001:2018
<b>Optics material:</b>	aluminium	<b>Plik LDT:</b>	<a href="#">Download</a>
<b>Optics:</b>	reflector		

Card creation date: 29 April 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 340/2023