

NECTRA LED PLUS 222MM 3250LM 830 IP44 AW 3H AT OPAL WHITE (25W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	517358
Ingress protection:	IP44
Nominal power [W]:	25
Luminous flux [lm]*:	3250
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	D
Material of the body:	PC, aluminium
Colour of the body:	white
Diffuser material:	PMMA

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

NECTRA LED PLUS 222MM 3250LM 830 IP44 AW 3H AT OPAL WHITE (25W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	ø222/70
Nominal power [W]:	25	Mounting dimensions [mm]:	ø195
Rated power of the luminaire [W]:	28	Impact resistance:	IK08
Supply voltage [V]:	110 - 277	Ingress protection:	IP44
Frequency [Hz]:	50 - 60	Mounting version:	recessed
Luminous flux [lm]:	3250	Working temperature [°C]:	from 0 to +35
Luminous efficacy [lm/W]:	116	Emergency lighting [h]:	3
Energy efficiency class:	D	Net weight [kg]:	0.930
Electrical protection class:	I	CE certificate:	340/2023
Colour temperature [K]:	3000	Warranty [years]:	2 / 0.5 (bateria)
Colour rendering index:	>80	Index:	517358
SDCM:	≤ 3	EAN:	5905963517358
Power factor:	0.95	Category type:	downlights
Charging time [h:min]:	24:00	Autotest:	yes
Beam angle [°]:	96	Operating mode:	M
Battery:	Ni-Mh	Luminaire rated power O_{min} [W]:	29.80
Diffuser material:	PMMA	AC voltage range [V]:	99 - 305
Diffuser type:	OPAL	DC voltage range [V]:	99 - 305
Optics material:	aluminium	LED lifespan L70B50 [h]:	80000
Optics:	reflector	LED lifespan L80B20 [h]:	55000
Material of the body:	PC, aluminium	LED lifespan L90B10 [h]:	30000
Colour of the body:	white	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Ring material:	PC	Warranty [years]:	2 / 0.5 (battery)
Ring colour:	white	Manual:	Download PDF

Card creation date: 23 February 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 340/2023