

# PROXIMA LED HV 20W BIAŁY IP65 RCR 4000K

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	546334/HV
Ingress protection:	IP65/54
Impact resistance:	IK10
Nominal power [W]:	20
Luminous flux [lm]*:	1450
Colour temperature [K]:	4000
Energy efficiency class:	F
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	OPAL

## CHARACTERISTICS

Surface mounted, round LED light fixture, high ingress protection class IP65 and an integrated energy-saving light source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). Optional equipment: radio motion sensor (RCR).

## APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. The luminaire will also work well as a general light source due to the decorative effect that it provides (indirect light distribution on the mounting surface). Two ring colors available: white or silver.


# PROXIMA LED HV 20W BIAŁY IP65 RCR 4000K

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ingress protection:	IP65/54
Nominal power [W]:	20	Mounting version:	surface
Rated power of the luminaire [W]:	20	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Motion sensor:	yes
Frequency [Hz]:	50 - 60	Net weight [kg]:	1.400
Luminous flux [lm]:	1450	Warranty [years]:	5
Luminous efficacy [lm/W]:	73	CE certificate:	<a href="#">47/2017</a>
Energy efficiency class:	F	Index:	546334/HV
Electrical protection class:	I	EAN:	5905963546334/HV
Colour temperature [K]:	4000	Category type:	bulkheads
Colour rendering index:	>80	Product line:	basic
Power factor:	0.53	ETIM class:	EC002892
Beam angle [°]:	120	LED lifespan L70B50 [h]:	110000
Diffuser material:	PC	LED lifespan L80B20 [h]:	72000
Diffuser type:	OPAL	LED lifespan L90B10 [h]:	36000
Material of the body:	PP	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	white	Warranty [years]:	2
Dimensions (H/W/T/S) [mm]:	ø390/95	Manual:	<a href="#">Download PDF</a>
Impact resistance:	IK10	PZH certificate:	<a href="#">HK/K/0389/01/2017</a>

## LIGHT CURVES



Card creation date: 31 March 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 47/2017



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)