

PROXIMA LED RCR 24W BIAŁY IP65 4000K

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|-----------|
| Index: | 311918/PA |
| Ingress protection: | IP65/54 |
| Impact resistance: | IK10 |
| Nominal power [W]: | 24 |
| Luminous flux [lm]*: | 2300 |
| Colour temperature [K]: | 4000 |
| Energy efficiency class: | F |
| Material of the body: | PP |
| Diffuser material: | PC |
| Diffuser type: | OPAL |

CHARACTERISTICS

Surface mounted, round LED light fixture, high ingress protection class IP65 and an integrated energy-saving light source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). Optional equipment: radio motion sensor (RCR).

APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. The luminaire will also work well as a general light source due to the decorative effect that it provides (indirect light distribution on the mounting surface). Two ring colors available: white or silver.

PROXIMA LED RCR 24W BIAŁY IP65 4000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|---------------------------|---|
| Nominal power [W]: | 24 | Working temperature [°C]: | from -20 to +35 |
| Light source: | LED module | Motion sensor: | yes |
| Colour temperature [K]: | 4000 | Net weight [kg]: | 1.320 |
| Luminous flux [lm]: | 2300 | Index: | 311918/PA |
| Rated power of the luminaire [W]: | 29 | Warranty [years]: | 5 |
| Supply voltage [V]: | 220-240 | CE certificate: | 387/2023 |
| Diffuser type: | OPAL | EAN: | 5905963311918/PA |
| Frequency [Hz]: | 50 - 60 | Category type: | bulkheads |
| Luminous efficacy [lm/W]: | 79 | Product line: | standard |
| Energy efficiency class: | F | ETIM class: | EC002892 |
| Electrical protection class: | I | LED lifespan L70B50 [h]: | 110000 |
| Colour rendering index: | >80 | LED lifespan L80B20 [h]: | 72000 |
| Power factor: | 0.90 | LED lifespan L90B10 [h]: | 36000 |
| Beam angle [°]: | 120 | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Diffuser material: | PC | Warranty [years]: | 2 |
| Material of the body: | PP | Manual: | Download PDF |
| Colour of the body: | white | PZH certificate: | HK/K/0389/01/2017 |
| Dimensions (H/W/T/S) [mm]: | ø390/95 | | |
| Impact resistance: | IK10 | | |
| Ingress protection: | IP65/54 | | |
| Mounting version: | surface | | |

LIGHT CURVES



Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 387/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl