

PROXIMA SMD LED 24W BIAŁY 4000K (UKŁAD OSRAM)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	546457/PA
Ingress protection:	IP65/54
Impact resistance:	IK10
Nominal power [W]:	24
Luminous flux [lm]*:	2300
Colour temperature [K]:	4000
Energy efficiency class:	F
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Surface mounted, round LED light fixture, high ingress protection class IP65 and an integrated energy-saving light source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). Optional equipment: radio motion sensor (RCR).

APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. The luminaire will also work well as a general light source due to the decorative effect that it provides (indirect light distribution on the mounting surface). Two ring colors available: white or silver.

PROXIMA SMD LED 24W BIAŁY 4000K (UKŁAD OSRAM)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	24	Working temperature [°C]:	from -20 to +35
Light source:	LED module	Net weight [kg]:	1.400
Colour temperature [K]:	4000	Index:	546457/PA
Luminous flux [lm]:	2300	Warranty [years]:	5
Rated power of the luminaire [W]:	29	CE certificate:	387/2023
Supply voltage [V]:	220-240	EAN:	5905963546457/PA
Diffuser type:	OPAL	Category type:	bulkheads
Frequency [Hz]:	50 - 60	Product line:	standard
Luminous efficacy [lm/W]:	79	ETIM class:	EC002892
Energy efficiency class:	F	LED lifespan L70B50 [h]:	110000
Electrical protection class:	I	LED lifespan L80B20 [h]:	72000
Colour rendering index:	>80	LED lifespan L90B10 [h]:	36000
Power factor:	0.90	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Beam angle [°]:	120	Warranty [years]:	2
Diffuser material:	PC	Manual:	Download PDF
Material of the body:	PP	PZH certificate:	HK/K/0389/01/2017
Colour of the body:	white		
Dimensions (H/W/T/S) [mm]:	ø390/95		
Impact resistance:	IK10		
Ingress protection:	IP65/54		
Mounting version:	surface		

LIGHT CURVES

