

MODO LED FI 116 360LM 830 IP67 I CL. 20° (6W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	x
Ingress protection:	IP67
Impact resistance:	IK09; IK10
Rated power of the luminaire [W]*:	6
Luminous flux [lm]*:	290 - 1850
Colour temperature [K]:	3000; 4000; 5000; 5700
Energy efficiency class:	E; F; G
Material of the body:	odlew aluminiowy; tworzywo sztuczne, stal
Diffuser material:	szkło hart.
Diffuser type:	transparentny

CHARACTERISTICS

Energy-saving, outdoor up-light fitting designed for ground mounting. It ensures economical and long-term operation without the need to replace light sources. It stands out with high ingress protection rating of IP67, thus making it resistant to immersion in water. In order to ensure optimum performance, it is made of aluminium and tempered glass which is additionally protected with a seal. Available in many light distribution options.

APPLICATION

The fitting is a popular choice both as facade lighting of various premises, like for example: office buildings, commercial buildings, car showrooms, religious buildings and also green spaces, parks and other architectural structures.

MODO LED FI 116 360LM 830 IP67 I CL. 20° (6W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	moduł LED	Ring colour:	srebrny
Rated power of the luminaire [W]:	6	Dimensions (H/W/T/S) [mm]:	ø116/150; ø173/149; ø185/123,6
Supply voltage [V]:	220-240	Mounting dimensions [mm]:	ø102/150; ø156,5/149; ø156.5x149; ø172/123,6
Frequency [Hz]:	50-60	Impact resistance:	IK09; IK10
Luminous flux [lm]:	290 - 1850	Ingress protection:	IP67
Energy efficiency class:	E; F; G	Accessories included:	assembly system for IoT, sealing, extraction, 2x cable cover, screws, dowels 6mm
Electrical protection class:	I	Net weight [kg]:	0.300; 1.300
Colour temperature [K]:	3000; 4000; 5000; 5700	Warranty [years]:	2
Beam angle [°]:	9; 15; 20; 30; 45; 45/35	Index:	x
Diffuser material:	szkło hart.	EAN:	x
Diffuser type:	transparentny	Category type:	accent lighting
Optics material:	PMMA	AC voltage range [V]:	220 - 240
Optics:	soczewka	Photobiological safety:	grupa ryzyka 1 (niskie ryzyko)
Material of the body:	odlew aluminiowy; tworzywo sztuczne, stal	Manual:	Download PDF
Ring material:	stal		

Card creation date:12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 86/2019



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl