

MODO LED FI 116 355LM 830 IP67 I CL. 9° (6W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	958007
Ingress protection:	IP67
Impact resistance:	IK09
Rated power of the luminaire [W]*:	6
Luminous flux [lm]*:	355
Colour temperature [K]:	3000
Energy efficiency class:	G
Material of the body:	odlew aluminiowy
Diffuser material:	tempered glass
Diffuser type:	transparent

CHARACTERISTICS

Energy-saving, outdoor up-light fitting designed for ground mounting. It ensures economical and long-term operation without the need to replace light sources. It stands out with high ingress protection rating of IP67, thus making it resistant to immersion in water. In order to ensure optimum performance, it is made of aluminium and tempered glass which is additionally protected with a seal. Available in many light distribution options.

APPLICATION

The fitting is a popular choice both as facade lighting of various premises, like for example: office buildings, commercial buildings, car showrooms, religious buildings and also green spaces, parks and other architectural structures.

MODO LED FI 116 355LM 830 IP67 I CL. 9° (6W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ring material:	Steel
Rated power of the luminaire [W]:	6	Ring colour:	silver
Colour temperature [K]:	3000	Mounting dimensions [mm]:	ø102/150
Luminous flux [lm]:	355	Impact resistance:	IK09
Supply voltage [V]:	220-240	Ingress protection:	IP67
Diffuser type:	transparent	Accessories included:	assembly system for IoT, sealing, extraction, 2x cable cover, screws, dowels 6mm
Frequency [Hz]:	50 - 60	Net weight [kg]:	0.300
Beam angle [°]:	9	Warranty [years]:	2
Dimensions (H/W/T/S) [mm]:	ø116/150	Index:	958007
Energy efficiency class:	G	EAN:	5905963958007
Electrical protection class:	I	Category type:	accent lighting
Diffuser material:	tempered glass	AC voltage range [V]:	220 - 240
Optics material:	PMMA	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics:	lens	Luminous efficacy [lm/W]:	59
Material of the body:	odlew aluminiowy	Manual:	Download PDF

Card creation date:12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 86/2019



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl