

# MODO LED FI 116 390LM 840 IP67 I CL. 9° (6W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	958014
<b>Ingress protection:</b>	IP67
<b>Impact resistance:</b>	IK09
<b>Rated power of the luminaire [W]*:</b>	6
<b>Luminous flux [lm]*:</b>	390
<b>Colour temperature [K]:</b>	4000
<b>Energy efficiency class:</b>	G
<b>Material of the body:</b>	odlew aluminiowy
<b>Diffuser material:</b>	tempered glass
<b>Diffuser type:</b>	transparent

## CHARACTERISTICS

Energy-saving, outdoor up-light fitting designed for ground mounting. It ensures economical and long-term operation without the need to replace light sources. It stands out with high ingress protection rating of IP67, thus making it resistant to immersion in water. In order to ensure optimum performance, it is made of aluminium and tempered glass which is additionally protected with a seal. Available in many light distribution options.

## APPLICATION

The fitting is a popular choice both as facade lighting of various premises, like for example: office buildings, commercial buildings, car showrooms, religious buildings and also green spaces, parks and other architectural structures.

# MODO LED FI 116 390LM 840 IP67 I CL. 9° (6W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Light source:</b>	LED module	<b>Ring colour:</b>	silver
<b>Rated power of the luminaire [W]:</b>	6	<b>Dimensions (H/W/T/S) [mm]:</b>	ø116/150
<b>Supply voltage [V]:</b>	220-240	<b>Mounting dimensions [mm]:</b>	ø102/150
<b>Frequency [Hz]:</b>	50 - 60	<b>Impact resistance:</b>	IK09
<b>Luminous flux [lm]:</b>	390	<b>Ingress protection:</b>	IP67
<b>Energy efficiency class:</b>	G	<b>Net weight [kg]:</b>	0.300
<b>Electrical protection class:</b>	I	<b>Warranty [years]:</b>	2
<b>Colour temperature [K]:</b>	4000	<b>Index:</b>	958014
<b>Beam angle [°]:</b>	9	<b>EAN:</b>	5905963958014
<b>Diffuser material:</b>	tempered glass	<b>Category type:</b>	accent lighting
<b>Diffuser type:</b>	transparent	<b>AC voltage range [V]:</b>	220 - 240
<b>Optics material:</b>	PMMA	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Optics:</b>	lens	<b>Luminous efficacy [lm/W]:</b>	65
<b>Material of the body:</b>	odlew aluminiowy	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Ring material:</b>	Steel		

Card creation date: 12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 86/2019