

MODO LED FI 116 410LM 857 IP67 I CL. 9° (6W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	958021
Ingress protection:	IP67
Impact resistance:	IK09
Rated power of the luminaire [W]*:	6
Luminous flux [lm]*:	410
Colour temperature [K]:	5700
Energy efficiency class:	G
Material of the body:	odlew aluminiowy
Diffuser material:	tempered glass
Diffuser type:	transparent

CHARACTERISTICS

Energy-saving, outdoor up-light fitting designed for ground mounting. It ensures economical and long-term operation without the need to replace light sources. It stands out with high ingress protection rating of IP67, thus making it resistant to immersion in water. In order to ensure optimum performance, it is made of aluminium and tempered glass which is additionally protected with a seal. Available in many light distribution options.

APPLICATION

The fitting is a popular choice both as facade lighting of various premises, like for example: office buildings, commercial buildings, car showrooms, religious buildings and also green spaces, parks and other architectural structures.

MODO LED FI 116 410LM 857 IP67 I CL. 9° (6W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ring colour:	silver
Rated power of the luminaire [W]:	6	Dimensions (H/W/T/S) [mm]:	ø116/150
Supply voltage [V]:	220-240	Mounting dimensions [mm]:	ø102/150
Frequency [Hz]:	50 - 60	Impact resistance:	IK09
Luminous flux [lm]:	410	Ingress protection:	IP67
Energy efficiency class:	G	Net weight [kg]:	0.300
Electrical protection class:	I	Warranty [years]:	2
Colour temperature [K]:	5700	Index:	958021
Beam angle [°]:	9	EAN:	5905963958021
Diffuser material:	tempered glass	Category type:	accent lighting
Diffuser type:	transparent	AC voltage range [V]:	220 - 240
Optics material:	PMMA	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics:	lens	Luminous efficacy [lm/W]:	68
Material of the body:	odlew aluminiowy	Manual:	Download PDF
Ring material:	Steel		

Card creation date:12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 86/2019



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl