## MODO LED FI 173 900LM 840 IP67 I CL. 15° (11W)

DETAILED CARD



### -0-

#### **TECHNICAL PARAMETERS**

Index:	958236	
Ingress protection:	IP67	
mpact resistance: IK10		
Rated power of the luminaire [W]*:	e luminaire [W]*: 11	
Luminous flux [lm]*:	900	
Colour temperature [K]:	4000	
Energy efficiency class:	ency class: F	
Material of the body:	odlew aluminiowy	
Diffuser material:	tempered glass	
Diffuser type:	transparent	

#### **CHARACTERISTICS**

Energy-saving, outdoor up-light fitting designed for ground mounting. It ensures economical and long-term operation without the need to replace light sources. It stands out with high ingress protection rating of IP67, thus making it resistant to immersion in water. In order to ensure optimum performance, it is made of aluminium and tempered glass which is additionally protected with a seal. Available in many light distribution options.

#### APPLICATION

The fitting is a popular choice both as facade lighting of various premises, like for example: office buildings, commercial buildings, car showrooms, religious buildings and also green spaces, parks and other architectural structures.



# MODO LED FI 173 900LM 840 IP67 I CL. 15° (11W)

DETAILED CARD

#### **TECHNICAL PARAMETERS TABLE**

			1
Light source:	LED module	Ring colour:	silver
Rated power of the luminaire [W]:	11	Dimensions (H/W/T/S) [mm]:	ø173/149
Supply voltage [V]:	220-240	Mounting dimensions [mm]:	ø156,5/149
Frequency [Hz]:	50 - 60	Impact resistance:	IK10
Luminous flux [lm]:	900	Ingress protection:	IP67
Energy efficiency class:	F	Net weight [kg]:	1.300
Electrical protection class:	1	Warranty [years]:	2
Colour temperature [K]:	4000	Index:	958236
Beam angle [°]:	15	EAN:	5905963958236
Diffuser material:	tempered glass	Category type:	accent lighting
Diffuser type:	transparent	AC voltage range [V]:	220 - 240
Optics material:	РММА	District size statu	Risk Group 1 (no photobiological hazard under normal behavioral
Optics:	lens	Photobiological safety:	limitation)
Material of the body:	odlew aluminiowy	Luminous efficacy [lm/W]:	82
Ring material:	Steel	Manual:	Download PDF

Card creation date: 12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

Certificate CE - Nr: 86/2019

This product is a subj

This product is a subject to electric and electronic waste equipment regulations (WEEE).

