# MODO LED FI 173 1020LM 857 IP67 I CL. 20° (11W)

DETAILED CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Index:** | 958274 |
| **Ingress protection:** | IP67 |
| **Impact resistance:** | IK10 |
| **Rated power of the luminaire [W]*:** | 11 |
| **Luminous flux [lm]*:** | 1020 |
| **Colour temperature [K]:** | 5700 |
| **Energy efficiency class:** | F |
| **Material of the body:** | odlew aluminiowy |
| **Diffuser material:** | tempered glass |
| **Diffuser type:** | transparent |

## CHARACTERISTICS

Energy-saving, outdoor up-light fitting designed for ground mounting. It ensures economical and long-term operation without the need to replace light sources. It stands out with high ingress protection rating of IP67, thus making it resistant to immersion in water. In order to ensure optimum performance, it is made of aluminium and tempered glass which is additionally protected with a seal. Available in many light distribution options.

## APPLICATION

The fitting is a popular choice both as facade lighting of various premises, like for example: office buildings, commercial buildings, car showrooms, religious buildings and also green spaces, parks and other architectural structures.

# MODO LED FI 173 1020LM 857 IP67 I CL. 20° (11W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | |
|---|---|
| **Light source:** | LED module |
| **Rated power of the luminaire [W]:** | 11 |
| **Supply voltage [V]:** | 220-240 |
| **Frequency [Hz]:** | 50 - 60 |
| **Luminous flux [lm]:** | 1020 |
| **Energy efficiency class:** | F |
| **Electrical protection class:** | I |
| **Colour temperature [K]:** | 5700 |
| **Beam angle [°]:** | 20 |
| **Diffuser material:** | tempered glass |
| **Diffuser type:** | transparent |
| **Optics material:** | PMMA |
| **Optics:** | lens |
| **Material of the body:** | odlew aluminiowy |
| **Ring material:** | Steel |

| | |
|---|---|
| **Ring colour:** | silver |
| **Dimensions (H/W/T/S) [mm]:** | ø173/149 |
| **Mounting dimensions [mm]:** | ø156,5/149 |
| **Impact resistance:** | IK10 |
| **Ingress protection:** | IP67 |
| **Net weight [kg]:** | 1.300 |
| **Warranty [years]:** | 2 |
| **Index:** | 958274 |
| **EAN:** | 5905963958274 |
| **Category type:** | accent lighting |
| **AC voltage range [V]:** | 220 - 240 |
| **Photobiological safety:** | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| **Luminous efficacy [lm/W]:** | 93 |
| **Manual:** | Download PDF |

Card creation date: 12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 86/2019

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl