MODO LED FI 173 835LM 857 IP67 I CL. 45° (11W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	958335
Ingress protection:	IP67
Impact resistance:	IK10
Rated power of the luminaire [W]*:	11
Luminous flux [lm]*:	835
Colour temperature [K]:	5700
Energy efficiency class:	F
Material of the body:	odlew aluminiowy
Diffuser material:	tempered glass
Diffuser type:	transparent

CHARACTERISTICS

Energy-saving, outdoor up-light fitting designed for ground mounting. It ensures economical and long-term operation without the need to replace light sources. It stands out with high ingress protection rating of IP67, thus making it resistant to immersion in water. In order to ensure optimum performance, it is made of aluminium and tempered glass which is additionally protected with a seal. Available in many light distribution options.

APPLICATION

The fitting is a popular choice both as facade lighting of various premises, like for example: office buildings, commercial buildings, car showrooms, religious buildings and also green spaces, parks and other architectural structures.

MODO LED FI 173 835LM 857 IP67 I CL. 45° (11W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Rated power of the luminaire [W]:	11
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	835
Energy efficiency class:	F
Electrical protection class:	I
Colour temperature [K]:	5700
Beam angle [°]:	45
Diffuser material:	tempered glass
Diffuser type:	transparent
Optics material:	PMMA
Optics:	lens
Material of the body:	odlew aluminiowy
Ring material:	Steel

Ring colour:	silver
Dimensions (H/W/T/S) [mm]:	ø173/149
Mounting dimensions [mm]:	ø156,5/149
Impact resistance:	IK10
Ingress protection:	IP67
Net weight [kg]:	1.300
Warranty [years]:	2
Index:	958335
EAN:	5905963958335
Category type:	accent lighting
AC voltage range [V]:	220 - 240
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Luminous efficacy [lm/W]:	76
Manual:	Download PDF

Card creation date: 12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 86/2019

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl