

# MODO LED FI 185 1320LM 830 IP67 I CL. 15° (18W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	958380
Ingress protection:	IP67
Impact resistance:	IK10
Rated power of the luminaire [W]*:	18
Luminous flux [lm]*:	1320
Colour temperature [K]:	3000
Energy efficiency class:	F
Material of the body:	odlew aluminiowy
Diffuser material:	tempered glass
Diffuser type:	transparent

## CHARACTERISTICS

Energy-saving, outdoor up-light fitting designed for ground mounting. It ensures economical and long-term operation without the need to replace light sources. It stands out with high ingress protection rating of IP67, thus making it resistant to immersion in water. In order to ensure optimum performance, it is made of aluminium and tempered glass which is additionally protected with a seal. Available in many light distribution options.

## APPLICATION

The fitting is a popular choice both as facade lighting of various premises, like for example: office buildings, commercial buildings, car showrooms, religious buildings and also green spaces, parks and other architectural structures.

# MODO LED FI 185 1320LM 830 IP67 I CL. 15° (18W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ring material:	Steel
Rated power of the luminaire [W]:	18	Ring colour:	silver
Supply voltage [V]:	220-240	Dimensions (H/W/T/S) [mm]:	ø185/123,6
Frequency [Hz]:	50 - 60	Mounting dimensions [mm]:	ø172/123,6
Luminous flux [lm]:	1320	Impact resistance:	IK10
Energy efficiency class:	F	Ingress protection:	IP67
Electrical protection class:	I	Warranty [years]:	2
Colour temperature [K]:	3000	Index:	958380
Beam angle [°]:	15	EAN:	5905963958380
Diffuser material:	tempered glass	Category type:	accent lighting
Diffuser type:	transparent	AC voltage range [V]:	220 - 240
Optics material:	PMMA	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics:	lens	Luminous efficacy [lm/W]:	73
Material of the body:	odlew aluminiowy	Manual:	<a href="#">Download PDF</a>

Card creation date:12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 86/2019



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl