MODO LED FI 185 1350LM 830 IP67 I CL. 20° (18W)

DETAILED CARD



TECHNICAL PARAMETERS

Index: 958403

Ingress protection: IP67

Impact resistance: IK10

Rated power of the luminaire [W]*: 18

Luminous flux [lm]*: 1350

Colour temperature [K]: 3000

Energy efficiency class:

Material of the body: odlew aluminiowy

Diffuser material: tempered glass

Diffuser type: transparent

CHARACTERISTICS

Energy-saving, outdoor up-light fitting designed for ground mounting. It ensures economical and long-term operation without the need to replace light sources. It stands out with high ingress protection rating of IP67, thus making it resistant to immersion in water. In order to ensure optimum performance, it is made of aluminium and tempered glass which is additionally protected with a seal. Available in many light distribution options.

APPLICATION

The fitting is a popular choice both as facade lighting of various premises, like for example: office buildings, commercial buildings, car showrooms, religious buildings and also green spaces, parks and other architectural structures.



MODO LED FI 185 1350LM 830 IP67 I CL. 20° (18W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| Light source: | LED module |
|-----------------------------------|------------------|
| Rated power of the luminaire [W]: | 18 |
| Supply voltage [V]: | 220-240 |
| Frequency [Hz]: | 50 - 60 |
| Luminous flux [lm]: | 1350 |
| Energy efficiency class: | F |
| Electrical protection class: | 1 |
| Colour temperature [K]: | 3000 |
| Beam angle [°]: | 20 |
| Diffuser material: | tempered glass |
| Diffuser type: | transparent |
| Optics material: | PMMA |
| Optics: | lens |
| Material of the body: | odlew aluminiowy |

| Ring material: | Steel |
|----------------------------|---|
| Ring colour: | silver |
| Dimensions (H/W/T/S) [mm]: | ø185/123,6 |
| Mounting dimensions [mm]: | ø172/123,6 |
| Impact resistance: | IK10 |
| Ingress protection: | IP67 |
| Warranty [years]: | 2 |
| Index: | 958403 |
| EAN: | 5905963958403 |
| Category type: | accent lighting |
| AC voltage range [V]: | 220 - 240 |
| Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Luminous efficacy [lm/W]: | 75 |
| Manual: | Download PDF |

Card creation date: 12 January 2021



