### MITRA LED 6450LM 4000K RM1 IP66 I KL. DALI (52W)

**DETAILED CARD** 





Light source:	LED module
Ingress protection:	IP66
Nominal power [W]:	52
Luminous flux [lm]*:	6450
Colour temperature [K]:	4000
SDCM:	3
Color rendering index (Ra) >:	80
Electrical protection class:	1
Energy efficiency class:	D
Material of the body:	PP+FG



LED fitting with high luminous efficiency and an energy-saving, integrated LED panel. Body made of polypropylene (PP) with glass fiber (GF), aluminum handle and polycarbonate diffuser (PC).

The lamp is available in two versions of light distribiution:

- general G1 with a frozen diffuser,
- road RM1 with a transparent diffuser and directional lens matrices made of PMMA.

IP66 ingress protection class and IK07 impact-rating features make this fitting shock-resistant (vandal-resistant). The integrated handle allows for top mounting to the pole. Colour of the body: gray (RAL 7010).

Standard equipped with:

- surge protection (SP10kV),
- H07RN-F cable with a length of 0.6 m and an IP66 quick connection.

#### **APPLICATION**

Fitting used in open spaces to lighten: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and mounting: post-top mounting. Mounting grip integrated with the fitting.



# MITRA LED 6450LM 4000K RM1 IP66 I KL. DALI (52W)


**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

Index:	956492
EAN:	5905963956492
Light source:	LED module
Nominal power [W]:	52
Rated power of the luminaire [W]:	51.30
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	6450
Luminous efficacy [lm/W]:	128
Energy efficiency class:	D
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.97
LED lifespan L70B50 [h]:	90000
Surge protection [kV]:	4
Diffuser material:	PC
Diffuser type:	transparent
Diffuser colour:	transparent
Optics material:	PMMA
Optics:	matrix lens
Material of the body:	PP+FG
Colour of the body:	grey

Dimensions (H/W/T/S) [mm]:	398/398/175
Mounting dimensions [mm]:	Ø60
Ingress protection:	IP66
Mounting version:	on the pole
Working temperature [°C]:	from -15 to +35
Diode size [mm]:	2835
Dimensions of single box [mm]:	400/400/175
Net weight [kg]:	2.100
Warranty [years]:	5
Category type:	Park and city lighting
Light distribution type:	RM1
Category of application:	parkings and bicycle paths
DIMM 1-10V:	yes
DIMM DALI:	yes
Beam angle [°]:	50000
Gross weight [kg]:	2.100
Permeability factor of the diffuser:	0.80
ETIM class:	EC000062
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
ULOR:	0%
Warranty [years]:	5
CE certificate:	100/2023
Manual:	Download PDF
Plik LDT:	Download

### **LIGHT CURVES**






## MITRA LED 6450LM 4000K RM1 IP66 I KL. DALI (52W)

**DETAILED CARD** 

#### **TECHNICAL DETAILS**







MITRA LED

MITRA LED MITRA LED

 $The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (-10\%) and (-10\%) are the presented product. \\ ^* Product data sheet does not constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (-10\%) are the presented product. \\ ^* Product data sheet does not constitute an offer. \\ ^* Parameter tolerance is +/- 10\% are the presented product. \\ ^* Product data sheet does not constitute an offer. \\ ^* Parameter tolerance is +/- 10\% are the presented product. \\ ^* Product data sheet does not constitute an offer. \\ ^* Parameter tolerance is +/- 10\% are the presented product. \\ ^* Product data sheet does not constitute an offer. \\ ^* Product data sheet does not constitute$ 



Page 3/3