


SPECTO LED EVO 900MM 2700LM PRM MAT IP40 840 (22W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	636431
Ingress protection:	IP40
Impact resistance:	IK02
Nominal power [W]:	22
Luminous flux [lm]*:	2700
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	steel

CHARACTERISTICS

Surface ceiling or wall mounted, high performance LED luminaire with compact space saving construction. Equipped with energy saving light sources LED. Powderpainted steel base, special multilayer prismatic diffuser combining high UV resistance PMMA cover and polypropylene optic system or single layer high UV resistance opal PMMA diffuser.

APPLICATION

Multi-purpose LED luminaire designed for indoor application for illuminating public use areas and corridors (administration buildings, schools and universities, health care buildings) Especially recommended for small space application or as complementary lighting. It is appropriate for new applications as well as replacing conventional T8 & T5 fittings on energy saving LED solutions. Fitting construction adapted for surface mounting (ceiling or wall) using included accessory installation kit.


SPECTO LED EVO 900MM 2700LM PRM MAT IP40 840 (22W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	636431	Material of the body:	steel
EAN:	5905963636431	Colour of the body:	white
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	900/45/84
Nominal power [W]:	22	Mounting dimensions [mm]:	695
Rated power of the luminaire [W]:	24	Impact resistance:	IK02
Supply voltage [V]:	220-240	Ingress protection:	IP40
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous flux [lm]:	2700	Working temperature [°C]:	from -17 to +35
Luminous efficacy [lm/W]:	113	Number on the palette [pcs]:	200
Energy efficiency class:	E	Net weight [kg]:	1.100
Electrical protection class:	I	Category type:	battens
Colour temperature [K]:	4000	ETIM class:	EC000109
Colour rendering index:	>80	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	50000	CE certificate:	337/2023
Diffuser material:	PMMA	Manual:	Download PDF
Diffuser type:	PRM MAT		

TECHNICAL PICTURES



Card creation date: 12 November 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 337/2023