

TUBE LED EVO 2 28W 4000K LS2 90 WIDE BEAM

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK08
Nominal power [W]:	28
Luminous flux [lm]*:	3100
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	PC
Diffuser type:	transparent

CHARACTERISTICS

LED luminaire system designed for suspended and surface mounting on walls and ceilings. Provides a combination of high illumination parameters and functionality. With its slim diameter of 42 mm possible to mount in hard-to-reach locations. Mounting is easy and quick. Due to the line lens, it is possible to adjust the fitting to different lighting requirements – three light distribution options: 90°, 60°, 30°.

APPLICATION

Luminaire intended for both outdoor and indoor use in industry areas and passageways. Provides good surface lighting and is perfect in situations that require eyesight concentration. Four housing sizes available. Suitable for mounting in all types of suspended ceilings (modular, plasterboard).


TUBE LED EVO 2 28W 4000K LS2 90 WIDE BEAM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	28	LED lifespan L70B50 [h]:	50000
Light source:	LED module	Optics material:	PMMA
Colour temperature [K]:	4000	Optics:	lens
Luminous flux [lm]:	3100	Material of the body:	PC
Rated power of the luminaire [W]:	32	Colour of the body:	silver
Diffuser type:	transparent	Mounting dimensions [mm]:	1328
Supply voltage [V]:	220-240	Impact resistance:	IK08
Beam angle [°]:	90	Ingress protection:	IP65
Frequency [Hz]:	50 - 60	Mounting version:	surface, suspended
Through wiring:	LS2	Net weight [kg]:	1.200
Luminous efficacy [lm/W]:	111	Warranty [years]:	5
Dimensions (H/W/T/S) [mm]:	42/45/1346	CE certificate:	226/2023
Energy efficiency class:	E	Index:	269271
Electrical protection class:	II	EAN:	5905963269271
Colour rendering index:	>80	Category type:	battens
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.92	Manual:	Download PDF
		Plik LDT:	Download

LIGHT CURVES



TUBE LED EVO 2 28W 4000K LS2 90 WIDE BEAM

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
267604	Tube LED EVO surface mounting bracket adjustable +/- 100 degrees
266591	Tube LED EVO electric suspension
266607	Tube LED EVO suspension cord
266829	Tube LED EVO Suspension (round box)
266492	Star connector TUBE LED EVO system
266485	Star connector TUBE LED EVO system matt white
266478	Star connector TUBE LED EVO system matt black



Tube LED EVO surface mounting bracket adjustable +/- 100 degrees (267604)



Tube LED EVO suspension cord (266607)



Star connector TUBE LED EVO system (266492)

Card creation date: 28 May 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 226/2023