

# MIMO 2 LED 1230MM 3350LM IP66 LS2 830 (23W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	100819
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK06
<b>Luminaire rated power <math>P_{min}</math> [W]:</b>	23.70
<b>Luminous flux [lm]*:</b>	3350
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	C
<b>Material of the body:</b>	PC

## CHARACTERISTICS

MIMO 2 LED represents the new generation of hermetic LED luminaires with very high IP66 tightness. The luminaire uses modern concepts to improve light distribution and temperature balance. Its design involved both proven solutions that affect high efficiency and durability, as well as efficient LED panels offering the best lighting level required and energy savings of up to 66%. The multilayer shade has been made of UV-resistant polycarbonate. Branded LED diodes and new LED modules have influence on a very high luminous efficacy: 150 lm/W. Optional: Through-Wiring series connection - LS2.

## APPLICATION

The multifunctional LED luminaire is designed for use in areas with increased dust and humidity. It is particularly suitable for industrial conditions, car parks (underground and multi-storey ones), sports stadiums, warehouses, transport terminals and underground passages. The luminaire is used both in new applications, as well as in replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended installation using standard equipment.

# MIMO 2 LED 1230MM 3350LM IP66 LS2 830 (23W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	100819	<b>Ingress protection:</b>	IP66
<b>EAN:</b>	50095963100819	<b>Mounting version:</b>	surface, suspended
<b>Light source:</b>	LED module	<b>Working temperature [°C]:</b>	from -20 to +35
<b>Nominal power [W]:</b>	23	<b>Net weight [kg]:</b>	0.360
<b>Rated power of the luminaire [W]:</b>	23.70	<b>CE certificate:</b>	<a href="#">151/2023</a>
<b>Supply voltage [V]:</b>	220-240	<b>Category type:</b>	battens
<b>Frequency [Hz]:</b>	50 - 60	<b>Operating mode:</b>	M
<b>Luminous flux [lm]:</b>	3350	<b>Luminous efficacy [lm/W]:</b>	141
<b>Energy efficiency class:</b>	C	<b>Electrical protection class:</b>	II
<b>Colour temperature [K]:</b>	3000	<b>Power factor:</b>	0.92
<b>Colour rendering index:</b>	>80	<b>Through wiring:</b>	LS2
<b>SDCM:</b>	≤ 3	<b>LED lifespan L70B50 [h]:</b>	143000
<b>Diffuser material:</b>	PC	<b>LED lifespan L80B20 [h]:</b>	90000
<b>Diffuser type:</b>	MAT	<b>LED lifespan L90B10 [h]:</b>	41000
<b>Material of the body:</b>	PC	<b>Wire type:</b>	H07RN-F 2x1,5
<b>Colour of the body:</b>	white	<b>Photobiological safety:</b>	RG0 - exempt (no photobiological hazard)
<b>Dimensions (H/W/T/S) [mm]:</b>	1230/45/50	<b>Warranty [years]:</b>	5
<b>Mounting dimensions [mm]:</b>	800	<b>Warranty [years]:</b>	5
<b>Impact resistance:</b>	IK06	<b>Manual:</b>	<a href="#">Download PDF</a>

# MIMO 2 LED 1230MM 3350LM IP66 LS2 830 (23W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
100673	MIMO 2 LED - double handle (set)
800ML208	IP68 High-bay PA 6.6 connector black DL06-3A-2Y



MIMO 2 LED - double handle (set) (100673)



IP68 High-bay PA 6.6 connector black DL06-3A-2Y (800ML208)

Card creation date: 19 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 151/2023