

# COMPACT LED EVO N 3150LM PLX II KL IP20 1200X250 840 (25W) AW 3H

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20
<b>Nominal power [W]:</b>	25
<b>Luminous flux [lm]*:</b>	3150
<b>Colour rendering index:</b>	>80
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	ABS
<b>Diffuser material:</b>	PS
<b>Diffuser type:</b>	OPAL

## CHARACTERISTICS

Compact LED luminaire designed for surface mounting or modular ceilings. Equipped with energy-saving LED modules and an evenly highlighted opal diffuser, providing low glare. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Standard Deviation Colour Matching (SDCM):  $\leq 3$ . COMPACT LED EVO N 1200x250 with nPRM nano-prismatic diffuser, can be used wherever low UGR is required.

## APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.

# COMPACT LED EVO N 3150LM PLX II KL IP20 1200X250 840 (25W) AW 3H

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	630347	<b>Ingress protection:</b>	IP20
<b>Light source:</b>	LED module	<b>Mounting version:</b>	surface mounted; recessed mounted in modular ceiling possible
<b>Nominal power [W]:</b>	25	<b>Working temperature [°C]:</b>	from 0 to +25
<b>Supply voltage [V]:</b>	220-240	<b>Emergency lighting [h]:</b>	3
<b>Frequency [Hz]:</b>	50 - 60	<b>Net weight [kg]:</b>	2.800
<b>Luminous flux [lm]:</b>	3150	<b>Warranty [years]:</b>	2 / 0.5 (bateria)
<b>Luminous efficacy [lm/W]:</b>	117	<b>EAN:</b>	5905963630347
<b>Energy efficiency class:</b>	D	<b>Category type:</b>	louvres
<b>Electrical protection class:</b>	II	<b>LED lifespan L70B50 [h]:</b>	132000
<b>Colour temperature [K]:</b>	4000	<b>LED lifespan L80B20 [h]:</b>	84000
<b>Colour rendering index:</b>	>80	<b>LED lifespan L90B10 [h]:</b>	42000
<b>Power factor:</b>	0.95	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Diffuser material:</b>	PS	<b>CE certificate:</b>	<a href="#">361/2023</a>
<b>Diffuser type:</b>	OPAL	<b>PZH certificate:</b>	<a href="#">B-BK-60212-0070/20 B-BK-60212-0042/20</a>
<b>Material of the body:</b>	ABS	<b>Warranty [years]:</b>	2 / 0.5 (battery)
<b>Colour of the body:</b>	white	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Dimensions (H/W/T/S) [mm]:</b>	1195/250/66	<b>ENEC Certificate:</b>	

Card creation date: 19 October 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 361/2023