

COMPACT LED EVO N 3550LM PLX II KL IP20 1200X250 830 (32W) AW 3H

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Nominal power [W]:	32
Luminous flux [lm]*:	3550
Colour rendering index:	80
Energy efficiency class:	E
Material of the body:	ABS
Diffuser material:	PS
Diffuser type:	OPAL

CHARACTERISTICS

Compact LED luminaire designed for surface mounting or modular ceilings. Equipped with energy-saving LED modules and an evenly highlighted opal diffuser, providing low glare. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Standard Deviation Colour Matching (SDCM): ≤3. COMPACT LED EVO N 1200x250 with nPRM nano-prismatic diffuser, can be used wherever low UGR is required.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.

COMPACT LED EVO N 3550LM PLX II KL IP20 1200X250 830 (32W) AW 3H

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	630330	Dimensions (H/W/T/S) [mm]:	1195/250/66
EAN:	5905963630330	Ingress protection:	IP20
Light source:	LED module	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Nominal power [W]:	32	Working temperature [°C]:	from 0 to +25
Supply voltage [V]:	220-240	Emergency lighting [h]:	3
Frequency [Hz]:	50 - 60	Net weight [kg]:	2.800
Luminous flux [lm]:	3550	Category type:	troffers
Luminous efficacy [lm/W]:	102	LED lifespan L70B50 [h]:	132000
Energy efficiency class:	E	LED lifespan L80B20 [h]:	84000
Electrical protection class:	II	LED lifespan L90B10 [h]:	42000
Colour temperature [K]:	3000	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Colour rendering index:	80	Warranty [years]:	2 / 0.5 (battery)
Power factor:	0.95	CE certificate:	361/2023
Diffuser material:	PS	ENEC Certificate:	
Diffuser type:	OPAL	PZH certificate:	B-BK-60212-0070/20 B-BK-60212-0042/20
Material of the body:	ABS	Manual:	Download PDF
Colour of the body:	white		