

# COMPACT LED EVO N 3550LM PLX II KL IP20 1200X250 830 (32W) AW 3H

DETAILED CARD



## TECHNICAL PARAMETERS

|                                 |      |
|---------------------------------|------|
| <b>Ingress protection:</b>      | IP20 |
| <b>Nominal power [W]:</b>       | 32   |
| <b>Luminous flux [lm]*:</b>     | 3550 |
| <b>Colour rendering index:</b>  | >80  |
| <b>Energy efficiency class:</b> | E    |
| <b>Material of the body:</b>    | ABS  |
| <b>Diffuser material:</b>       | PS   |
| <b>Diffuser type:</b>           | OPAL |

## CHARACTERISTICS

Compact LED luminaire designed for surface mounting or modular ceilings. Equipped with energy-saving LED modules and an evenly highlighted opal diffuser, providing low glare. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Standard Deviation Colour Matching (SDCM):  $\leq 3$ . COMPACT LED EVO N 1200x250 with nPRM nano-prismatic diffuser, can be used wherever low UGR is required.

## APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.

# COMPACT LED EVO N 3550LM PLX II KL IP20 1200X250 830 (32W) AW 3H

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                     |            |                                   |                                                                             |
|-------------------------------------|------------|-----------------------------------|-----------------------------------------------------------------------------|
| <b>Nominal power [W]:</b>           | 32         | <b>Colour of the body:</b>        | white                                                                       |
| <b>Index:</b>                       | 630330     | <b>Dimensions (H/W/T/S) [mm]:</b> | 1195/250/66                                                                 |
| <b>Light source:</b>                | LED module | <b>Ingress protection:</b>        | IP20                                                                        |
| <b>Colour temperature [K]:</b>      | 3000       | <b>Mounting version:</b>          | surface mounted; recessed mounted in modular ceiling possible               |
| <b>Luminous flux [lm]:</b>          | 3550       | <b>Working temperature [°C]:</b>  | from 0 to +25                                                               |
| <b>Diffuser type:</b>               | OPAL       | <b>Net weight [kg]:</b>           | 2.800                                                                       |
| <b>Supply voltage [V]:</b>          | 220-240    | <b>Warranty [years]:</b>          | 2 / 0.5 (bateria)                                                           |
| <b>Diffuser material:</b>           | PS         | <b>EAN:</b>                       | 5905963630330                                                               |
| <b>Frequency [Hz]:</b>              | 50 - 60    | <b>Category type:</b>             | louvres                                                                     |
| <b>Emergency lighting [h]:</b>      | 3          | <b>LED lifespan L70B50 [h]:</b>   | 132000                                                                      |
| <b>Luminous efficacy [lm/W]:</b>    | 102        | <b>LED lifespan L80B20 [h]:</b>   | 84000                                                                       |
| <b>Energy efficiency class:</b>     | E          | <b>LED lifespan L90B10 [h]:</b>   | 42000                                                                       |
| <b>Electrical protection class:</b> | II         | <b>Photobiological safety:</b>    | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| <b>Colour rendering index:</b>      | >80        | <b>CE certificate:</b>            | <a href="#">361/2023</a>                                                    |
| <b>Power factor:</b>                | 0.95       | <b>PZH certificate:</b>           | <a href="#">B-BK-60212-0070/20 B-BK-60212-0042/20</a>                       |
| <b>Material of the body:</b>        | ABS        | <b>Warranty [years]:</b>          | 2 / 0.5 (battery)                                                           |
|                                     |            | <b>Manual:</b>                    | <a href="#">Download PDF</a>                                                |
|                                     |            | <b>ENEC Certificate:</b>          |                                                                             |

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 361/2023