

COMPACT LED EVO N 6800LM PLX DALI I KL. IP20

1200X250 840 (58W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Nominal power [W]:	58
Luminous flux [lm]*:	6800
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Diffuser material:	PS
Diffuser type:	OPAL

CHARACTERISTICS

Compact LED luminaire designed for surface mounting or modular ceilings. Equipped with energy-saving LED modules and an evenly highlighted opal diffuser, providing low glare. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Standard Deviation Colour Matching (SDCM): ≤3. COMPACT LED EVO N 1200x250 with nPRM nano-prismatic diffuser, can be used wherever low UGR is required.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.

COMPACT LED EVO N 6800LM PLX DALI I KL. IP20

1200X250 840 (58W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	58	Colour of the body:	white
Index:	628986	Dimensions (H/W/T/S) [mm]:	1195/250/66
Light source:	LED module	Ingress protection:	IP20
Colour temperature [K]:	4000	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Luminous flux [lm]:	6800	Working temperature [°C]:	from -20 to +35
Diffuser type:	OPAL	Net weight [kg]:	2.300
Supply voltage [V]:	220-240	Warranty [years]:	5
Diffuser material:	PS	EAN:	5905963628986
Frequency [Hz]:	50 - 60	Category type:	louvres
DIMM DALI:	yes	LED lifespan L70B50 [h]:	115000
Luminous efficacy [lm/W]:	113	LED lifespan L80B20 [h]:	72000
Energy efficiency class:	E	LED lifespan L90B10 [h]:	35000
Electrical protection class:	I	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour rendering index:	>80	CE certificate:	361/2023
SDCM:	≤ 3	PZH certificate:	B-BK-60212-0070/20 B-BK-60212-0042/20
Power factor:	0.98	Warranty [years]:	5
Material of the body:	ABS	Manual:	Download PDF
		ENEC Certificate:	PL BBJ/009/2021/M1
		Plik LDT:	

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 361/2023