COMPACT LED EVO N 6600LM RCR IP20 PLX I KL 1200X250 840 (58W) CORRIDOR

DETAILED CARD

TECHNICAL PARAMETERS

Ingress protection:	IP20
Impact resistance:	IK07
Nominal power [W]:	58
Luminous flux [lm]*:	6600
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	E
Material of the body:	ABS
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Neue kompakte LED-Leuchte für die Aufputzmontage. Ausgestattet mit energiesparenden LED-Module und einem gleichmäßig beleuchteten, opalisierenden Diffusor. Die Leuchte wurde aus Kunststoff gefertigt. Für die Montage und den elektrischen Anschluss muss der Diffusor nicht entfernt werden. Spezielle Halterungen für die Montage der COMPACT Leuchte zur Aufputzmontage, für den Einsatz auf unebenen Decken. Diese Griffe gewährleisten eine solide Montage und gleichzeitige Einhaltung des Abstands zwischen Decke und Lampe. COMPACT LED EVO N 1200x250 mit nPRM Nano-Prismen-Diffusor, überall dort einsetzbar, wo ein niedriger UGR gefordert ist.

APPLICATION

Die Leuchte ist für den Inneneinsatz in allgemeinen Büro- oder Nutzräumen vorgesehen. Bewährt sich hervorragend als Hauptlichtquelle und fördert Arbeiten, die Konzentration erfordern. Die Leuchte wird sowohl für neue Investitionen als auch beim Austausch von herkömmlichen Leuchten mit hohem Energieverbrauch gegen energiesparende LED-Lösungen eingesetzt.

COMPACT LED EVO N 6600LM RCR IP20 PLX I KL 1200X250 840 (58W) CORRIDOR

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	630583
EAN:	5905963630583
Light source:	LED module
Nominal power [W]:	58
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	6600
Luminous efficacy [lm/W]:	113
Energy efficiency class:	E
Electrical protection class:	I
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.95
Diffuser material:	PC
Diffuser type:	OPAL
Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	1195/250/66
Impact resistance:	IK07

Ingress protection:	IP20
Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Working temperature [°C]:	od -20 do +35
Corridor function:	yes
Motion sensor:	yes
DIMM DALI:	yes
Category type:	troffers
LED lifespan L70B50 [h]:	115000
LED lifespan L80B10 [h]:	72000
LED lifespan L90B10 [h]:	35000
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Warranty [years]:	5
CE certificate:	361/2023
ENEC Certificate:	
PZH certificate:	B-BK-60112-0326/2026
Environmental Product Declaration (EPD):	944/2026
Manual:	Download PDF
ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Plik LDT:	Download

Card creation date: 15 October 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 361/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl