

# COMPACT LED EVO N RCR 3550LM PLX II KL IP20

## 1200X250 830 (32W)

DETAILED CARD



### TECHNICAL PARAMETERS

Ingress protection:	IP20
Nominal power [W]:	32
Luminous flux [lm]*:	3550
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Diffuser material:	PS
Diffuser type:	OPAL

### CHARACTERISTICS

Compact LED luminaire designed for surface mounting or modular ceilings. Equipped with energy-saving LED modules and an evenly highlighted opal diffuser, providing low glare. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Standard Deviation Colour Matching (SDCM): ≤3. COMPACT LED EVO N 1200x250 with nPRM nano-prismatic diffuser, can be used wherever low UGR is required.

### APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.

# COMPACT LED EVO N RCR 3550LM PLX II KL IP20

## 1200X250 830 (32W)

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	630453	Dimensions (H/W/T/S) [mm]:	1195/250/66
EAN:	5905963630453	Ingress protection:	IP20
Light source:	LED module	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Nominal power [W]:	32	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Motion sensor:	yes
Frequency [Hz]:	50 - 60	UGR (4H8H):	<19
Luminous flux [lm]:	3550	Net weight [kg]:	2.300
Luminous efficacy [lm/W]:	100	Category type:	louvres
Energy efficiency class:	E	LED lifespan L70B50 [h]:	132000
Electrical protection class:	II	LED lifespan L80B20 [h]:	84000
Colour temperature [K]:	3000	LED lifespan L90B10 [h]:	42000
Colour rendering index:	>80	Photobiological safety:	RG0 - exempt (no photobiological hazard)
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.95	CE certificate:	<a href="#">361/2023</a>
Diffuser material:	PS	ENEC Certificate:	
Diffuser type:	OPAL	PZH certificate:	<a href="#">B-BK-60212-0070/20</a> <a href="#">B-BK-60212-0042/20</a>
Material of the body:	ABS	Manual:	<a href="#">Download PDF</a>
Colour of the body:	white	Plik LDT:	<a href="#">Download</a>