

COMPACT LED EVO N RCR 4750LM PLX II KL IP20 1200X250 830 (44W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Nominal power [W]:	44
Luminous flux [lm]*:	4750
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	E
Material of the body:	ABS
Diffuser material:	PS
Diffuser type:	OPAL

CHARACTERISTICS

Compact LED luminaire designed for surface mounting or modular ceilings. Equipped with energy-saving LED modules and an evenly highlighted opal diffuser, providing low glare. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Standard Deviation Colour Matching (SDCM): ≤ 3 . COMPACT LED EVO N 1200x250 with nPRM nano-prismatic diffuser, can be used wherever low UGR is required.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.

COMPACT LED EVO N RCR 4750LM PLX II KL IP20 1200X250 830 (44W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	630491	Dimensions (H/W/T/S) [mm]:	1195/250/66
EAN:	5905963630491	Ingress protection:	IP20
Light source:	LED module	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Nominal power [W]:	44	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Motion sensor:	yes
Frequency [Hz]:	50 - 60	Net weight [kg]:	2.300
Luminous flux [lm]:	4750	Category type:	troffers
Luminous efficacy [lm/W]:	100	LED lifespan L70B50 [h]:	125000
Energy efficiency class:	E	LED lifespan L80B20 [h]:	82000
Electrical protection class:	II	LED lifespan L90B10 [h]:	40000
Colour temperature [K]:	3000	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Color rendering index (Ra) >:	80	Warranty [years]:	5
SDCM:	3	CE certificate:	361/2023
Power factor:	0.95	ENEC Certificate:	
Diffuser material:	PS	PZH certificate:	B-BK-60212-0070/20 B-BK- 60212-0042/20
Diffuser type:	OPAL	Manual:	Download PDF
Material of the body:	ABS	Plik LDT:	Download
Colour of the body:	white		

Card creation date: 11 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 361/2023