

# COMPACT LED EVO N RCR 5150LM PLX II KL IP20 1200X250 840 (44W)

DETAILED CARD



## TECHNICAL PARAMETERS

Ingress protection:	IP20
Nominal power [W]:	44
Luminous flux [lm]*:	5150
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	E
Material of the body:	ABS
Diffuser material:	PS
Diffuser type:	OPAL

## CHARACTERISTICS

Compact LED luminaire designed for surface mounting or modular ceilings. Equipped with energy-saving LED modules and an evenly highlighted opal diffuser, providing low glare. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Standard Deviation Colour Matching (SDCM): ≤3. COMPACT LED EVO N 1200x250 with nPRM nano-prismatic diffuser, can be used wherever low UGR is required.

## APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.

# COMPACT LED EVO N RCR 5150LM PLX II KL IP20 1200X250 840 (44W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	630484	Dimensions (H/W/T/S) [mm]:	1195/250/66
EAN:	5905963630484	Ingress protection:	IP20
Light source:	LED module	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Nominal power [W]:	44	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Motion sensor:	yes
Frequency [Hz]:	50 - 60	Net weight [kg]:	2.300
Luminous flux [lm]:	5150	Category type:	troffers
Luminous efficacy [lm/W]:	109	LED lifespan L70B50 [h]:	125000
Energy efficiency class:	E	LED lifespan L80B20 [h]:	82000
Electrical protection class:	II	LED lifespan L90B10 [h]:	40000
Colour temperature [K]:	4000	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Color rendering index (Ra) >:	80	Warranty [years]:	5
SDCM:	3	CE certificate:	<a href="#">361/2023</a>
Power factor:	0.95	ENEC Certificate:	
Diffuser material:	PS	PZH certificate:	<a href="#">B-BK-60212-0070/20 B-BK-60212-0042/20</a>
Diffuser type:	OPAL	Manual:	<a href="#">Download PDF</a>
Material of the body:	ABS	Plik LDT:	<a href="#">Download</a>
Colour of the body:	white		