


QUBE 1 LED 1615LM 857 IP65 I CL. 32° (18W) RAL 7037

DETAILED CARD



TECHNICAL PARAMETERS

Index:	959554
Ingress protection:	IP65
Impact resistance:	IK06
Rated power of the luminaire [W]*:	18
Luminous flux [lm]*:	1615
Colour temperature [K]:	5700
Energy efficiency class:	F
Material of the body:	aluminium
Diffuser material:	tempered glass
Diffuser type:	transparent

CHARACTERISTICS

This energy-saving, outdoor accent LED fitting ensures economical and long-term operation without the need to replace light sources. It has high ingress protection rating of IP65—from dust ingress and water jets from any direction. The ingress protection is ensured by its design—aluminium body and tempered glass additionally protected with a seal. The fitting is available in many light distribution options and two lighting versions:

- up or down
- up and down

APPLICATION

The fitting for wall mounting (directly to the surface by means of wall plugs) is designed especially for accent outdoor lighting of facades of: hotels, offices, apartment buildings but also private houses, passageways and entrance areas.


QUBE 1 LED 1615LM 857 IP65 I CL. 32° (18W) RAL 7037

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Colour of the body:	RAL7037
Rated power of the luminaire [W]:	18	Mounting dimensions [mm]:	100/136
Colour temperature [K]:	5700	Impact resistance:	IK06
Luminous flux [lm]:	1615	Ingress protection:	IP65
Supply voltage [V]:	220-240	Warranty [years]:	2
Frequency [Hz]:	50 - 60	Index:	959554
Beam angle [°]:	32	EAN:	5905963959554
Dimensions (H/W/T/S) [mm]:	204/136	Category type:	accent lighting
Energy efficiency class:	F	Version:	up or down
Electrical protection class:	I	AC voltage range [V]:	220 - 240
Diffuser material:	tempered glass	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser type:	transparent	Luminous efficacy [lm/W]:	90
Optics material:	PC	Manual:	Download PDF
Optics:	Reflektor	Plik LDT:	Download
Material of the body:	aluminium		

LIGHT CURVES



Card creation date:12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 89/2019



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl