

DOBLO LED 36W DALI WHITE 4000K

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|---------------------|
| Ingress protection: | IP20 |
| Impact resistance: | IK07 |
| Nominal power [W]: | 36 |
| Luminous flux [lm]*: | 3850 |
| Colour rendering index: | >80 |
| SDCM: | ≤ 3 |
| Energy efficiency class: | E |
| Material of the body: | powder coated steel |
| Diffuser material: | PS |
| Diffuser type: | OPAL |

CHARACTERISTICS

Decorative lighting fitting with the effect of indirect light constituting 30% of the total light output of the luminaire. It was made of powder coated sheet steel and equipped with an economical LED GO! panel. Specification: color temperature: 3000K/4000K; CRI>80; LED panels lifespan 50 000h (L70B50) for $t_a=25^{\circ}\text{C}$. DIMM/DALI options available on request.

APPLICATION

A versatile indoor luminaire designed for office rooms and areas of general public use. It is perfect for representational spaces.

DOBLO LED 36W DALI WHITE 4000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|---|------------------------------|
| Nominal power [W]: | 36 | LED lifespan L70B50 [h]: | 50000 |
| Index: | 094095 | Diffuser material: | PS |
| Colour temperature [K]: | 4000 | Material of the body: | powder coated steel |
| Light source: | LED module | Dimensions (H/W/T/S) [mm]: | 1180/200/52 |
| Luminous flux [lm]: | 3850 | Impact resistance: | IK07 |
| Diffuser type: | OPAL | Ingress protection: | IP20 |
| Rated power of the luminaire [W]: | 38 | Mounting version: | suspended |
| Colour of the body: | white | Working temperature [°C]: | from -20 to +35 |
| Supply voltage [V]: | 220-240 | Net weight [kg]: | 6.700 |
| DIMM DALI: | 1 | Warranty [years]: | 5 |
| Frequency [Hz]: | 50 - 60 | CE certificate: | 371/2023 |
| Energy efficiency class: | E | EAN: | 5905963094095 |
| Luminous efficacy [lm/W]: | 101 | Category type: | louvres |
| Electrical protection class: | I | Luminaire rated power θ_{min} [W]: | 36 |
| Colour rendering index: | >80 | Manual: | Download PDF |
| SDCM: | ≤ 3 | Plik LDT: | Pobierz |

Card creation date: 02 December 2019

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 371/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl