

DOBLO LED 50W DALI GREY 3000K

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Impact resistance:	IK07
Nominal power [W]:	50
Luminous flux [lm]*:	4950
Colour rendering index:	80
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	powder coated steel
Diffuser material:	PS
Diffuser type:	OPAL

CHARACTERISTICS

Decorative lighting fitting with the effect of indirect light constituting 30% of the total light output of the luminaire. It was made of powder coated sheet steel and equipped with an economical LED GO! panel. Specification: color temperature: 3000K/4000K; CRI>80; LED panels lifespan 50 000h (L70B50) for ta=25°C. DIMM/DALI options available on request.

APPLICATION

A versatile indoor luminaire designed for office rooms and areas of general public use. It is perfect for representational spaces.

DOBLO LED 50W DALI GREY 3000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	094149	Material of the body:	powder coated steel
Light source:	LED module	Colour of the body:	grey
Nominal power [W]:	50	Dimensions (H/W/T/S) [mm]:	1180/200/52
Rated power of the luminaire [W]:	54	Impact resistance:	IK07
Supply voltage [V]:	220-240	Ingress protection:	IP20
Frequency [Hz]:	50 - 60	Mounting version:	suspended
Luminous flux [lm]:	4950	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	91	DIMM DALI:	yes
Energy efficiency class:	F	Net weight [kg]:	6.700
Electrical protection class:	I	Warranty [years]:	5
Colour temperature [K]:	3000	CE certificate:	371/2023
Colour rendering index:	80	EAN:	5905963094149
SDCM:	≤ 3	Category type:	troffers
LED lifespan L70B50 [h]:	50000	Luminaire rated power 0min [W]:	50
Diffuser material:	PS	Manual:	Download PDF
Diffuser type:	OPAL	Plik LDT:	Download

LIGHT CURVES

