

SWING LED 15W 4000K BIAŁY KORYTARZOWY

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|--------------------------|--------------------------|
| Light source: | COB LED |
| Ingress protection: | IP40 |
| Nominal power [W]: | 15 |
| Luminous flux [lm]*: | 1450 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | >80 |
| Energy efficiency class: | E |
| Material of the body: | plastic, aluminum, steel |
| Colour of the body: | white |

CHARACTERISTICS

Recessed frameless downlight fitting equipped with modern and energy-saving light source COB LED. The body made of plastic, steel and aluminium ensures a long-term operation of the fitting. The diffuser made of highly transparent PMMA guarantees high luminous flux and ensures optimal conditions for the LED operation. Due to the possibility of adjusting the light direction vertically up to 30° and horizontally (turn) up to 355°, four options of diffuser to choose: 65°, 25°, 59°/92°, as well as modern and elegant design, the fitting is suitable for a variety of applications.

APPLICATION

Recessed fitting suitable for mounting in plasterboard ceilings, dedicated for indoor use as a basic or accent lighting. Due to modern and elegant design and the possibility of choosing the optimal light distribution, the fitting is ideal for offices, commercial buildings and passageways.


SWING LED 15W 4000K BIAŁY KORYTARZOWY

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|--------------------------|---------------------------------|------------------------------|
| Light source: | COB LED | Colour of the body: | white |
| Nominal power [W]: | 15 | Dimensions (H/W/T/S) [mm]: | ø178/163 |
| Rated power of the luminaire [W]: | 15 | Mounting dimensions [mm]: | ø196 |
| Supply voltage [V]: | 220-240 | Ingress protection: | IP40 |
| Frequency [Hz]: | 50 - 60 | Mounting version: | recessed |
| Luminous flux [lm]: | 1450 | Working temperature [°C]: | from -17 to +35 |
| Luminous efficacy [lm/W]: | 96 | Corridor function: | yes |
| Energy efficiency class: | E | Net weight [kg]: | 1.200 |
| Electrical protection class: | I | CE certificate: | 142/2020 |
| Colour temperature [K]: | 4000 | Warranty [years]: | 5 |
| Colour rendering index: | >80 | Index: | 091063 |
| Power factor: | 0.95 | EAN: | 5905963091063 |
| LED lifespan L70B50 [h]: | 50000 | Category type: | downlights |
| Beam angle [°]: | 59-92 | Luminaire rated power 0min [W]: | 15 |
| Diffuser type: | PRM | Manual: | Download PDF |
| Material of the body: | plastic, aluminum, steel | | |

LIGHT CURVES



Card creation date: 22 October 2019

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 142/2020

 **LENA**
LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl