SWING LED 20W DALI 4000K BIAŁY WĄSKOKĄTNY

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	COB LED
Ingress protection:	IP40
Nominal power [W]:	20
Luminous flux [lm]*:	1280
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	G
Material of the body:	plastic, aluminum, steel
Colour of the body:	white

CHARACTERISTICS

Recessed frameless downlight fitting equipped with modern and energy-saving light source COB LED. The body made of plastic, steel and aluminium ensures a long-term operation of the fitting. The diffuser made of highly transparent PMMA guarantees high luminous flux and ensures optimal conditions for the LED operation. Due to the possibility of adjusting the ligt direction vertically up to 30° and horizontally (turn) up to 355°, four options of diffuser to choose: 65°, 25°, 59°/92°, as well as modern and elegant design, the fitting is suitable for a variety of applications.

APPLICATION

Recessed fitting suitable for mounting in plasterboard ceilings, dedicated for indoor use as a basic or accent lighting. Due to modern and elegant design and the possibility of choosing the optimal light distribution, the fitting is ideal for offices, commercial buildings and passageways.


SWING LED 20W DALI 4000K BIAŁY WĄSKOKĄTNY

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	COB LED	**Colour of the body:**	white
Nominal power [W]:	20	**Dimensions (H/W/T/S) [mm]:**	ø178/163
Rated power of the luminaire [W]:	20	**Mounting dimensions [mm]:**	ø196
Supply voltage [V]:	220-240	**Ingress protection:**	IP40
Frequency [Hz]:	50 - 60	**Mounting version:**	recessed
Luminous flux [lm]:	1280	**Working temperature [°C]:**	from -17 to +35
Luminous efficacy [lm/W]:	64	**DIMM DALI:**	yes
Energy efficiency class:	G	**Net weight [kg]:**	1.200
Electrical protection class:	I	**CE certificate:**	142/2020
Colour temperature [K]:	4000	**Warranty [years]:**	5
Colour rendering index:	>80	**Index:**	091223
Power factor:	0.95	**EAN:**	5905963091223
LED lifespan L70B50 [h]:	50000	**Category type:**	downlights
Beam angle [°]:	25	**Luminaire rated power 0min [W]:**	20
Diffuser type:	MAT	**Manual:**	Download PDF
Material of the body:	plastic, aluminum, steel		

LIGHT CURVES



Card creation date: 22 October 2019

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 142/2020

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl