MIMO 2 LED 670MM 1900LM IP66 830 (13W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	100741
Ingress protection:	IP66
Impact resistance:	IK06
Luminaire rated power 0min [W]:	15.30
Luminous flux [lm]*:	1900
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	D
Material of the body:	PC

CHARACTERISTICS

MIMO 2 LED represents the new generation of hermetic LED luminaires with very high IP66 tightness. The luminaire uses modern concepts to improve light distribution and temperature balance. Its design involved both proven solutions that affect high efficiency and durability, as well as efficient LED panels offering the best lighting level required and energy savings of up to 66%. The multilayer shade has been made of UV-resistant polycarbonate. Branded LED diodes and new LED modules have influence on a very high luminous efficacy: 150 lm/W.
Optional: Through-Wiring series connection - LS2.

APPLICATION

The multifunctional LED luminaire is designed for use in areas with increased dust and humidity. It is particularly suitable for industrial conditions, car parks (underground and multi-storey ones), sports stadiums, warehouses, transport terminals and underground passages. The luminaire is used both in new applications, as well as in replacing traditional fluorescent luminaires with energy-saving LED solutions Its design is adapted for surface and suspended installation using standard equipment.

MIMO 2 LED 670MM 1900LM IP66 830 (13W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	13
Rated power of the luminaire [W]:	15.30
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	1900
Energy efficiency class:	D
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Diffuser material:	PC
Diffuser type:	matt
Material of the body:	PC
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	670/45/50
Mounting dimensions [mm]:	400
Impact resistance:	IK06
Ingress protection:	IP66
Mounting version:	surface, suspended
Working temperature [°C]:	from -20 to +35

Net weight [kg]:	0.210
Index:	100741
Category type:	battens
Operating mode:	M
Light distribution type:	open space
Luminous efficacy [lm/W]:	124
Electrical protection class:	II
Power factor:	0.92
EAN:	5905963100741
LED lifespan L70B50 [h]:	116000
LED lifespan L80B10 [h]:	72000
LED lifespan L90B10 [h]:	31000
Photobiological safety:	RG0 - exempt (no photobiological hazard)
CE certificate:	151/2023
Warranty [years]:	5
Environmental Product Declaration (EPD):	944/2026
Manual:	Download PDF
ISO Certificates:	9001:2015. 14001:2015, 45001:2018, 50001:2018
Plik LDT:	Download

MIMO 2 LED 670MM 1900LM IP66 830 (13W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
100673	MIMO 2 LED - double handle (set)
800ML208	IP68 High-bay PA 6.6 connector black DL06-3A-2Y



MIMO 2 LED - double handle (set) (100673)



IP68 High-bay PA 6.6 connector black DL06-3A-2Y (800ML208)

Card creation date: 29 April 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 151/2023

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl