


# MIMO 2 LED 670MM 2050LM IP66 840 (13W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	100727
Ingress protection:	IP66
Impact resistance:	IK06
Luminaire rated power $P_{\text{max}}$ [W]:	15.30
Luminous flux [lm]*:	2050
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	D
Material of the body:	PC

## CHARACTERISTICS

MIMO 2 LED represents the new generation of hermetic LED luminaires with very high IP66 tightness. The luminaire uses modern concepts to improve light distribution and temperature balance. Its design involved both proven solutions that affect high efficiency and durability, as well as efficient LED panels offering the best lighting level required and energy savings of up to 66%. The multilayer shade has been made of UV-resistant polycarbonate. Branded LED diodes and new LED modules have influence on a very high luminous efficacy: 150 lm/W. Optional: Through-Wiring series connection - LS2.

## APPLICATION

The multifunctional LED luminaire is designed for use in areas with increased dust and humidity. It is particularly suitable for industrial conditions, car parks (underground and multi-storey ones), sports stadiums, warehouses, transport terminals and underground passages. The luminaire is used both in new applications, as well as in replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended installation using standard equipment.

# MIMO 2 LED 670MM 2050LM IP66 840 (13W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	100727	Ingress protection:	IP66
EAN:	5905963100727	Mounting version:	surface, suspended
Light source:	LED module	Working temperature [°C]:	from -20 to +35
Nominal power [W]:	13	Net weight [kg]:	0.260
Rated power of the luminaire [W]:	15.30	CE certificate:	<a href="#">151/2023</a>
Supply voltage [V]:	220-240	Category type:	battens
Frequency [Hz]:	50 - 60	Operating mode:	M
Luminous flux [lm]:	2050	Luminous efficacy [lm/W]:	134
Energy efficiency class:	D	Electrical protection class:	II
Colour temperature [K]:	4000	Power factor:	0.92
Color rendering index (Ra) >:	80	LED lifespan L70B50 [h]:	116000
SDCM:	3	LED lifespan L80B20 [h]:	72000
Diffuser material:	PC	LED lifespan L90B10 [h]:	31000
Diffuser type:	matt	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Material of the body:	PC	Warranty [years]:	5
Colour of the body:	white	Warranty [years]:	5
Dimensions (H/W/T/S) [mm]:	670/45/50	Manual:	<a href="#">Download PDF</a>
Mounting dimensions [mm]:	400	Plik LDT:	<a href="#">Download</a>
Impact resistance:	IK06		

# MIMO 2 LED 670MM 2050LM IP66 840 (13W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
100673	MIMO 2 LED - double handle (set)
800ML208	IP68 High-bay PA 6.6 connector black DL06-3A-2Y



MIMO 2 LED - double handle (set) (100673)



IP68 High-bay PA 6.6 connector black DL06-3A-2Y (800ML208)

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 151/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl