

MADERA 3 LED 620X350MM 2450LM 830 IP44 OPAL WHITE (21W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44
Nominal power [W]:	21
Luminous flux [lm]*:	2450
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	powder coated steel
Diffuser material:	PS
Diffuser type:	OPAL
Mounting version:	surface

CHARACTERISTICS

Surface mounted, square LED fitting with high luminous flux, made of steel sheet, powder-coated grey; equipped with energy-saving light source LED-GO!. OPAL or PRM PMMA diffuser ensures even light distribution and no glare effect. Decorative fitting available in two diffuser sizes; optional equipment: radio motion sensor (RCR).

APPLICATION

Surface-mounted luminaire intended for indoor use in offices or common rooms. Suitable as a general light source in representative rooms. Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. Product designed for surface mounting either on ceilings or on walls.

MADERA 3 LED 620X350MM 2450LM 830 IP44 OPAL WHITE (21W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	21	SDCM:	≤ 3
Index:	497735	Diffuser material:	PS
Colour temperature [K]:	3000	Material of the body:	powder coated steel
EAN:	5905963497735	Mounting dimensions [mm]:	265/495
Luminous flux [lm]:	2450	Ingress protection:	IP44
Light source:	LED module	Mounting version:	surface
Diffuser type:	OPAL	Net weight [kg]:	4.100
Rated power of the luminaire [W]:	23	Warranty [years]:	5
Colour of the body:	white	CE certificate:	254/2023
Supply voltage [V]:	220-240	Category type:	louvres
Dimensions (H/W/T/S) [mm]:	620/350/68	Luminaire rated power Omin [W]:	22.60
Frequency [Hz]:	50 - 60	LED lifespan L70B50 [h]:	95000
Energy efficiency class:	E	LED lifespan L80B20 [h]:	60000
Luminous efficacy [lm/W]:	108	LED lifespan L90B10 [h]:	29000
Electrical protection class:	I	Light distribution type:	lambertian
Colour rendering index:	>80	Manual:	Download PDF
		Plik LDT:	Pobierz

Card creation date: 20 January 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 254/2023