


# MADERA 3 LED 620X620MM 4250LM 840 IP44 OPAL GRAY (34W)

## DETAILED CARD



### TECHNICAL PARAMETERS

Ingress protection:	IP44
Nominal power [W]:	34
Luminous flux [lm]*:	4250
Color rendering index (Ra) >:	80
Energy efficiency class:	D
Material of the body:	powder coated steel
Diffuser material:	PS
Diffuser type:	OPAL
Mounting version:	surface

### CHARACTERISTICS

Surface mounted, square LED fitting with high luminous flux, made of steel sheet, powder-coated grey; equipped with energy-saving light source LED-GO!. OPAL or PRM PMMA diffuser ensures even light distribution and no glare effect. Decorative fitting available in two diffuser sizes; optional equipment: radio motion sensor (RCR).

### APPLICATION

Surface-mounted luminaire intended for indoor use in offices or common rooms. Suitable as a general light source in representative rooms. Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. Product designed for surface mounting either on ceilings or on walls.

# MADERA 3 LED 620X620MM 4250LM 840 IP44 OPAL GRAY (34W)

## DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	497322	Colour of the body:	grey
EAN:	5905963497322	Dimensions (H/W/T/S) [mm]:	620/620/68
Light source:	LED module	Mounting dimensions [mm]:	535/495
Nominal power [W]:	34	Ingress protection:	IP44
Rated power of the luminaire [W]:	36	Mounting version:	surface
Supply voltage [V]:	220-240	Net weight [kg]:	6.600
Frequency [Hz]:	50 - 60	Warranty [years]:	5
Luminous flux [lm]:	4250	CE certificate:	<a href="#">254/2023</a>
Luminous efficacy [lm/W]:	120	Category type:	troffers
Energy efficiency class:	D	Luminaire rated power $\Omega_{min}$ [W]:	35.30
Electrical protection class:	I	LED lifespan L70B50 [h]:	95000
Colour temperature [K]:	4000	LED lifespan L80B20 [h]:	60000
Color rendering index (Ra) >:	80	LED lifespan L90B10 [h]:	29000
Diffuser material:	PS	Light distribution type:	lambertian
Diffuser type:	OPAL	Manual:	<a href="#">Download PDF</a>
Material of the body:	powder coated steel	Plik LDT:	<a href="#">Download</a>

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 254/2023