

COMPACT SOLID LED 2950LM PLX II KL. IP20 620X620 840 (24W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	009631
Ingress protection:	IP20
Impact resistance:	IK07
Nominal power [W]:	24
Luminous flux [lm]*:	2950
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	A+
Material of the body:	ABS + powder coated steel sheet
Diffuser material:	PC

CHARACTERISTICS

Compact LED luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED GO! panels and an evenly highlighted opal or prismatic difuser, providing low glare (UGR<19)*. Made of powder coated steel sheet and plastic. Assembly or electrical connection does not require removing the diffuser.

* The UGR coefficient is met for the typical use of the luminaire

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting's design is suitable for mounting in 600x600 modular ceilings.

COMPACT SOLID LED 2950LM PLX II KL. IP20 620X620 840 (24W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	24	Colour of the body:	white
Index:	009631	Dimensions (H/W/T/S) [mm]:	71/620/620
Colour temperature [K]:	4000	Mounting dimensions [mm]:	500x300
Light source:	LED module	Impact resistance:	IK07
Luminous flux [lm]:	2950	Ingress protection:	IP20
Diffuser type:	OPAL	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Electrical protection class:	II	Net weight [kg]:	4.200
Frequency [Hz]:	50 - 60	Warranty [years]:	5
Energy efficiency class:	A+	Category type:	louvres
Luminous efficacy [lm/W]:	118	Luminaire rated power P_{min} [W]:	25
Colour rendering index:	>80	UGR (4H8H):	< 19
SDCM:	≤ 3	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Power factor:	0.95	Warranty [years]:	5
LED lifespan L70B50 [h]:	132000	Manual:	Download PDF
Diffuser material:	PC	CE certificate:	363/2023
Material of the body:	ABS + powder coated steel sheet	Plik LDT:	

COMPACT SOLID LED 2950LM PLX II KL. IP20 620X620 840 (24W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
009624	COMPACT SOLID – steel frame



COMPACT SOLID – steel frame (009624)

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 363/2023