# COMPACT SOLID LED 3800LM PLX II KL. IP20 620X620 840 (32W)

**DETAILED CARD** 





## **TECHNICAL PARAMETERS**

Index:	009662
Ingress protection:	IP20
Impact resistance:	IK07
Nominal power [W]:	32
Luminous flux [lm]*:	3800
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	A+
Material of the body:	ABS + powder coated steel sheet

PC

## **CHARACTERISTICS**

Compact LED luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED GO! panels and an evenly highlighted opal or prismatic difuser, providing low glare (UGR<19)\*. Made of powder caoated steel sheet and plastic. Assembly or electrical connection does not require removing the diffuser.

\* The UGR coefficient is met for the typical use of the luminaire

### APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting's design is suitable for mounting in 600x600 modular ceilings.



Diffuser material:

# **COMPACT SOLID LED 3800LM PLX II KL. IP20 620X620 840** (32W)


**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

Index:	009662
Light source:	LED module
Nominal power [W]:	32
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [Im]:	3800
Luminous efficacy [lm/W]:	113
Energy efficiency class:	A+
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.95
LED lifespan L70B50 [h]:	132000
Diffuser material:	PC
Diffuser type:	OPAL

Material of the body:	ABS + powder coated steel sheet
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	71/620/620
Mounting dimensions [mm]:	500x300
Impact resistance:	IK07
Ingress protection:	IP20
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Net weight [kg]:	4.200
Category type:	troffers
Luminaire rated power 0min [W]:	33
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Warranty [years]:	5
CE certificate:	363/2023
Manual:	Download PDF
Plik LDT:	Download

### **LIGHT CURVES**






# COMPACT SOLID LED 3800LM PLX II KL. IP20 620X620 840 (32W)

**DETAILED CARD** 

### **ACCESSORIES AVAILABLE**

index	Name
009624	COMPACT SOLID – steel frame



COMPACT SOLID – steel frame (009624)

Card creation date: 14 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

