LUNGO 825 LM 24 ST FI60 H250 I KL IP20 NT BLACK 830 (10W)

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	COB LED
Ingress protection:	IP20
Nominal power [W]:	10
Luminous flux [lm]*:	825
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Energy efficiency class:	F
Material of the body:	aluminium
Colour of the body:	black
Diffuser material:	PMMA

CHARACTERISTICS

The family of lungo luminaires will make each interior stylish and original. The option to combine different sizes and colours of luminaires allows creating original compositions which will be a decorative embellishment of rooms arranged in a modern way.

APPLICATION

The luminaire is intended for indoor traffic zones included in table 5.1 of the EN12464 standard.

LUNGO 825 LM 24 ST FI60 H250 I KL IP20 NT BLACK 830 (10W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	COB LED
Nominal power [W]:	10
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	825
Luminous efficacy [lm/W]:	82
Energy efficiency class:	F
Electrical protection class:	I
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.99
LED lifespan L70B50 [h]:	40000
Beam angle [°]:	24
Diffuser material:	PMMA
Diffuser type:	PRM
Optics material:	PMMA

Optics:	lens
Material of the body:	aluminium
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	60/250
Mounting dimensions [mm]:	36
Ingress protection:	IP20
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Net weight [kg]:	0.400
CE certificate:	229/2023
Index:	645532
EAN:	5905963637001
Category type:	decorative fixtures
Warranty [years]:	2
Manual:	Download PDF
Plik LDT:	Download

LIGHT CURVES



Card creation date: 17 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 229/2023

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl