LUNGO 860 LM 24 ST FI60 H145 I KL IP20 SUSPENDED BLACK AND GOLD 840 (10W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	645785
Ingress protection:	IP20
Nominal power [W]:	10
Luminous flux [lm]*:	860
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	F

CHARACTERISTICS

The family of lungo luminaires will make each interior stylish and original. The option to combine different sizes and colours of luminaires allows creating original compositions which will be a decorative embellishment of rooms arranged in a modern way.

APPLICATION

The luminaire is intended for indoor traffic zones included in table 5.1 of the EN12464 standard.


LUNGO 860 LM 24 ST FI60 H145 I KL IP20 SUSPENDED BLACK AND GOLD 840 (10W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	COB LED	**Diffuser type:**	PRM
Nominal power [W]:	10	**Dimensions (H/W/T/S) [mm]:**	60/145/1500
Supply voltage [V]:	220-240	**Ingress protection:**	IP20
Frequency [Hz]:	50 - 60	**Mounting version:**	suspended
Luminous flux [lm]:	860	**Working temperature [°C]:**	from -20 to +35
Luminous efficacy [lm/W]:	86	**Net weight [kg]:**	0.400
Energy efficiency class:	F	**CE certificate:**	161/2019
Electrical protection class:	I	**Index:**	645785
Colour temperature [K]:	4000	**Category type:**	downlights
Colour rendering index:	>80	**Warranty [years]:**	2
SDCM:	≤ 3	**Manual:**	Download PDF
Beam angle [°]:	24		

LIGHT CURVES



Card creation date: 08 December 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 161/2019

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl