TYTAN MULTI LED 1150 5000-8700LM 840 IP66 AW 3H

DETAILED CARD



TECHNICAL PARAMETERS

Index:	358845
Ingress protection:	IP66
Impact resistance:	IK09
Nominal power [W] - range:	26/33/40/47
Luminous flux of the luminaire [lm] - range:	5000/6250/7500/8700
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Material of the body:	PC
Diffuser material:	PC

CHARACTERISTICS

TYTAN MULTI LED is a fitting from NEXT GEN line, which is a new generation of fittings in LED technology. The fitting, designed from scratch, allows new solutions improving the light distribution and temperature balance. Branded LED diodes and new LED modules have influence on a very high luminous efficacy: up to 175 lm/W. It guarantees the best required lighting level and energy saving up to 68%. The solution based on integration of the diffuser and LED module is applied in the fitting. The fitting has a lot of facilities making the mounting easier and faster: the system of diffuser suspension, adjustable mounting brackets ensuring the mounting tolerance +/-50mm. Standard equipment of the fitting: clips made of stainless steel (INOX). Motion sensor mounting height: up to 5 meters.The MULTI luminaire version allows individual configuration: thanks to the built-in microswitch, it is possible to choose one of four settings (nominal power of the fitting [W] / luminous flux of the fitting [lm]):
13W-24W - 1. 13W/2500 lm; 2. 17W/3150 lm; 3. 20W/3750 lm; 4. 24W/4350 lm;
26W-47W - 1. 26W/5000 lm; 2. 33W/6250 lm; 3. 40W/7500 lm; 4. 47W/8700 lm;
21W-29W - 1. 16W/3150 lm; 2. 21W/3900 lm; 3. 25W/4700 lm; 4. 29W/5450 lm;
33W-59W - 1. 33W/6300 lm; 2. 41W/7850 lm; 3. 50W/9350 lm; 4. 59W/10900 lm.

APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level) , sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.

TYTAN MULTI LED 1150 5000-8700LM 840 IP66 AW 3H


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	358845
EAN:	5905963358845
Light source:	LED module
Nominal power [W] - range:	26/33/40/47
Rated power [W] - range:	28.9/36.1/43.4/50.3
Luminous flux of the luminaire [lm] - range:	5000/6250/7500/8700
Luminous efficacy [lm/W]:	173
Energy efficiency class:	B
Electrical protection class:	I
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.91
Exchangeable source:	yes
Diffuser material:	PC
Diffuser type:	matt
Diffuser colour:	white
Optics material:	PC
Material of the body:	PC
Colour of the body:	grey

Dimensions (H/W/T/S) [mm]:	1152/85/80
Impact resistance:	IK09
Ingress protection:	IP66
Mounting version:	surface, suspended
Working temperature [°C]:	from -20 to +35
Emergency lighting [h]:	3
Warranty [years]:	2 / 0.5 (bateria)
Category type:	battens
LED lifespan L70B50 [h]:	177000
LED lifespan L80B10 [h]:	111000
LED lifespan L90B10 [h]:	53000
ETIM class:	EC000109
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Warranty [years]:	2 / 0.5 (battery)
CE certificate:	152/2019
PZH certificate:	B-BK-60212-0152/20
HACCP:	852/2004
ENEC Certificate:	0310/ENEC/23
Manual:	Download PDF

LIGHT CURVES



TYTAN MULTI LED 1150 5000-8700LM 840 IP66 AW 3H

DETAILED CARD

TECHNICAL DETAILS




regulowane uchwyty / adjustable handles / einstellbare Halterungen



system zwieszania klosza / suspension system of the diffuser / hängende Diffusor



wybór miejsca zasilania / choosing a place of power supply / Stromversorgungsanschluss von mehreren Seite möglich




tytan multi led

TYTAN MULTI LED 1150 5000-8700LM 840 IP66 AW 3H

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
907913	TYTAN LED. ATLAS LED - protective grid 1152mm
907920	TYTAN LED. ATLAS LED - protective grid 1432mm
16000507	Breathable gland gray M20*1.5 IP68
358937	TYTAN MULTI LED 1150mm 2500-4300lm 840 - lighting module
358944	TYTAN MULTI LED 1150mm 5000-8700lm 840 - lighting module
358951	TYTAN MULTI LED 1450mm 3150-5450lm 840 - lighting module
60000006	M16 stuffing box plug various PA black M-16 - BPM-21
80000378	Cable gland PG 13.5 Titanium PA 6.6 gray with nut



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



TYTAN LED. ATLAS LED - protective grid 1152mm (907913)



TYTAN LED. ATLAS LED - protective grid 1432mm (907920)



Breathable gland gray M20*1.5 IP68 (16000507)



TYTAN MULTI LED 1150mm 2500-4300lm 840 - lighting module (358937)



TYTAN MULTI LED 1150mm 5000-8700lm 840 - lighting module (358944)



TYTAN MULTI LED 1450mm 3150-5450lm 840 - lighting module (358951)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 152/2019

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl