## INDUSTRY IP66 LED 1150MM 13600LM 840 (85W)

**DETAILED CARD** 



#### **TECHNICAL PARAMETERS**

Index: 552038
Ingress protection: IP66
Nominal power [W]: 85
Luminous flux [Im]\*: 13600
Colour temperature [K]: 4000
Color rendering index (Ra) >: 80
SDCM: 3
Energy efficiency class: C

aluminium

glass

**CHARACTERISTICS** 

INDUSTRY IP66 LED is a hermetic beam from the NEXT GEN line, which is a new generation of lamps dedicated to LED technology. The body, made from scratch, made of aluminum profile and subjected to anodization process, provides the luminaire with strength and solidity, and the narrow side profile allows installation in hard to reach places. LEDs from a reputable manufacturer and new LED modules have an impact on very high luminous efficacy: up to 163 lm / W. This guarantees that the required lighting level is achieved and that significant energy savings are achieved. The lampshade is made of UV resistant tempered glass. The combination of materials (aluminum and toughened glass) and a non-dismantled construction with an external connector provides the luminaire with high resistance to harsh environmental conditions.

Suitable for surface and suspended mounting.

Options: any RAL color; diffuser made of PC or PMMA.

### **APPLICATION**

The multi-purpose LED luminaire has been designed for use in areas requiring high dust and water resistance. It is especially recommended for use in rooms intended for medical and laboratory purposes as well as in industrial premises.



Material of the body:

Diffuser material:

# INDUSTRY IP66 LED 1150MM 13600LM 840 (85W)


**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

	1
Index:	552038
EAN:	5905963552038
Rated power of the luminaire [W]:	92.20
Luminous flux [lm]:	13600
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	148
Energy efficiency class:	С
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
LED lifespan L70B50 [h]:	108000
LED lifespan L80B20 [h]:	71000
LED lifespan L90B10 [h]:	33000
Beam angle [°]:	110
Diffuser material:	glass

Diffuser type:	transparent
Diffuser colour:	transparent
Optics material:	PMMA
Material of the body:	aluminium
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	1150/63/55
Impact resistance:	IK08
Ingress protection:	IP66
Working temperature [°C]:	from -15 to +35
The number of implement units:	1
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	5
CE certificate:	<u>146/2023</u>
PZH certificate:	B-BK-60212-0322/20
Manual:	Download PDF
Plik LDT:	Download

### **LIGHT CURVES**





# INDUSTRY IP66 LED 1150MM 13600LM 840 (85W)

**DETAILED CARD** 

#### **ACCESSORIES AVAILABLE**

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)

 $The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute and (a) a constitute and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance$ 

